

ABBREVIATIONS (REFER TO CONSULTANT DRAWINGS FOR ADDITIONAL ABBREVIATIONS) AC. TILE ACOUSTIC TILE ADJUSTABLE LAV. LAM. ALUM. ALUMINUM LAMINATE ANCHOR BOLT APPROX. M.B. MACHINE BOLT APPROXIMATELY ASPHALTIC CONCRETE M.H. MFG. A.C. A.F.F. MANHOLE MANUFACTURER ABOVE FINISHED FLOOR MASONRY OPENING MATERIAI BLKG. BLOCKING MAXIMUM BOARD **MECHANICAL** BOT. BLDG. BOTTOM METAL BUILDING MINIMUM MISCELLANEOUS CABINET MOUNTED CAST IRON CATCH BASIN NOT IN CONTRACT N.T.S. NOT TO SCALE CLG. CEILING NO. or # NUMBER CEMENT CENTER TO CENTER C.C or O.C. OBSCURE ON CENTER CENTERLINE CER. TILE CERAMIC TILE OPENING C.O. C.O.T.G. CI FANOUT OPPOSITE CLEANOUT TO GRADE OPPOSITE HAND O.F.O.S. OUTSIDE FACE OF STUD CLEAR RDW C.W. REDWOOD O.D. OVERFLOW DRAIN and/or COLD WATER OUTSIDE DIAMETER O.F.C.I. COL. CONC. C.P. COLUMN OWNER FURNISHED and CONCRETE CONTRACTOR INSTALLED CONCRETE PIPE CONSTRUCTION CONSTRUCTION HEART P.A.F. POWDER ACTUATED CONSTRUCTION JOINT **FASTENER** CONT. CONTINUOUS PLATE PLASTER CTR. CTSK. COUNTER PLYWOOD COUNTER SUNK PW/PLYWD. D.A. DISABLED ACCESS PROPERTY LINE PENNY (NAILS) DETAIL DIA. or Ø DIAMETER P.V.C. POLY VINYL CHLORIDE DIMENSION DISHWASHER DISPOSAL R. or RAD. DOOR RAIN WATER LEADER DOWNSPOUT REDWOOD REINFORCED CONCRETE DRINKING FOUNTAIN and/or DOUGLAS FIR REINF. REINFORCING REQUIRED EACH ROOF DRAIN EACH WAY E.W. ELECT. RM. R.O. ROOM ELECTRIC or ELECTRICAL ROUGH OPENING E.W.C. ELECTRIC WATER RND. or Ø ROUND ROUND HEAD METAL COOLER R.H.M.S. **ELEVATION** SCREW R.H.W.S. ROUND HEAD WOOD ENCLOSE and/or ENCL. ENCLOSURE **EQUAL** S.T.S.M.S. SELF TAPPING SHEET EQUIP. **EQUIPMENT** METAL SCREW EXISTING SHEATHING **EXPANSION** S.M.S. SHEET METAL SCREW EXPANSION JOINT SHUT OFF VALVE **EXPOSED** S.O.V. EXT. **EXTERIOR** SIMILAR SOLID CORE FACE OF CONCRETE SPECIFICATIONS FACE OF MASONRY SQ. or Ø SQUARE F.O.S. STAINLESS STEEL FACE OF STUD STANDARD FIRE EXTINGUISHER FIRE EXTINGUISHER STRUCT. STRUCTURAL F.H.C. FIRE HOSE CABINET TELEPHONE FLAT HEAD METAL TELEPHONE TERMINA SCREW FLAT HEAD WOOD BOARD F.H.W.S. TERRAZZO SCREW FL. or FLR. FLOOR T.&G. TONGUE & GROOVE FLOOR DRAIN TOOLED JOINT T.J. T.O.B. T.O.C. FOOTING TOP OF BEAM FND. FOUNDATION TOP OF CURB or CONCRETE T.O.S. GALVANIZED TOP OF STEEL GALVANIZED IRON or SHEATHING T.O.W. GAUGE TOP OF WALK GLASS TYPICAL GLU-LAM GLUE-LAMINATED GRADE U.O.N. UNLESS OTHERWISE GYP. BD. GYPSUM BOARD NOTED HARDWARE V.T.R. **VENT THROUGH ROOF** VERT. HEIGHT VERTICAL H.C. **HOLLOW CORE** VERTICAL GRAIN V.G. V.C.T. H.M. **HOLLOW METAL** VINYL COMPOSITION HORIZ. HORIZONTAL V.C.P. VITRIFIED CLAY PIPE H.B. HOSE BIBB

V.W.C.

W.W.M..

VINYL WALL COVERING

WELDED WIRE MESH

WATER CLOSET

WATER HEATER

WATERPROOF

WITHOUT

WOOD

HR.

INSUL.


HOUR


INSULATION


INTERIOR

INVERT

JOINT







PURNAMA RESIDENCE 1832 CHANNING AVE. PALO ALTO

> Alto Palo Channing

1832

Davide Giannella A.I.A





644 N. Santa Cruz Ave. Suite Los Gatos, California 95030 T. 408-219-0601

dg@acadia-architecture.com

ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN MATERIAL APPEARING HEREIN CONSTITUTE THE ORIGINAL, UNPUBLISHED WORK OF ACADIA-ARCHITECTURE AND THE SAME MAY NOT BE DUPLICATED, USED, OR DISCLOSED WITHOUT THE WRITTEN CONSENT OF ACADIA-ARCHITECTURE



DEFERRED APPROVAL ITEMS


PROJECT INFORMATION

APN	003 41 047
COUNTY	SANTA CLARA
ZONING DISTRICT	R-1 100
FLOOD ZONE	AH13.8
HISTORIC DISTRICT	No
OCCUPANCY	R-3 + U-1
BUILDING TYPE	V-B
AVERAGE SLOPE	0
LOT SIZE	5,852
ALLOWED FLOOR AREA	2,505 sq.ft.
MAX COVERAGE	2,048 sq.ft.
MIN. SETBACK	F= 20' S=6' R=20'
MAXIMUM HEIGHT (PROPOSED)	+- 26' 4"
FIRST FLOOR	1,273 sq.ft.
SECOND FLOOR	998 sq.ft.
GARAGE	233 sq.ft.
FLOOR AREA (sq.ft.) including garage	2,504 sq.ft.
PROPOSED COVERAGE (sq.ft.)	(1st Floor 1,273) + (Garage 233) + (Front Porch 294)= 1,800
	1,800 / 5,852 = 30%



Proposed East Elevation

A 1.0



1- ALL DOWNSPOUTS AND FOUNDATION PERIMETER DRAINS TO BE CONNECTED TO SPLASH BLOCKS AWAY FROM BUILDING

5-SLOPE GRADE AWAY FROM BUILDING 5% FOR A DISTANCE OF 5' AWAY FROM BUILDING. PROVIDE 2% SLOPE ON

7- ENSURE PROPER LOT DRAINAGE PER CHAPTER 11 CPC 2013 FOR LOCATION OF CATCH BASINS TO THE PROPERTY

NEW EXTERIOR / INTERIOR WALL

MIN. 1/2" GYPSUM BOARD TYPE X OVER STUDS FROM CURB TO UNDERSIDE OF ROOF SHEATING

1-CONTRACTOR TO VERIFY ALL DIMENSIONS IN FIELD AND NOTIFY ARCHITECT OF ANY DISCREPANCY BEFORE ANY CONSTRUCTION

LINES WITH SURVEYOR AND USE SETBACKS FOR ADDITION LAY-OUT

1) GRADE FOR PURPOSE OF ESTABLISHING DAYLIGHT PLAN SHALL BE AN AVERAGE OF THE GRADE AT THE MIDPOINBT OF THE BUILDING AND GRADE AT THE

DRAINAGE NOTES

2- SURFACE DRAINAGE TO FLOW THROUGH GRASS SWALES 3- NOT USED

4-ONLY TREES INDICATED TO BE REMOVED SHALL BE REMOVED

IMPERVIOUS SURFACES

6-NOT USED

8-THE RUNOFF SHOULD REMAIN ON THE PROPERTY NOT BE TAKEN TO A PUBLIC WAY.

GRAPHIC KEY:

EXISTING WALL TO REMAIN

1HR FIRE RESISTIVE WALL CONSTRUCTION
AT WALLS BETWEEN GARAGE AND LIVABLE SPACE:

DIMENSIONS NOTE

2- CONTRACTOR TO STAKE PROPERTY

<u>NOTE</u>

CLOSEST POINT ON THE ADJACENT LOT

acadia architecture

Davide Giannella A.I.A.

Palo

Ave.

Channing

1832


644 N. Santa Cruz Ave. Suite 6 Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com


ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN MATERIAL APPEARING HEREIN CONSTITUTE THE ORIGINAL, UNPUBLISHED WORK OF ACADIA-ARCHITECTURE AND THE SAME MAY NOT BE DUPLICATED, USED, OR DISCLOSED WITHOUT THE WRITTEN CONSENT OF ACADIA-ARCHITECTURE




A 1.1





OOR AREA CALC	ULATION		
SECTION # (SHAPE)	SIDE A	SIDE B	FLOOR AREA OF SECTION FOOTPRINT
01- RECTANGLE	10'-10"	21'- 6 1/2"	233 sq.ft.
			TOTAL GARAGE
			233 sq.ft.
02- RECTANGLE	16'-9 1/2"	10'-2"	170 sq.ft.
03- RECTANGLE	6'-3 1/2"	7'-2"	45 sq.ft.
04- RECTANGLE	2'-5"	4'-4 1/2"	11 sq.ft.
05- RECTANGLE	30'-3 1/2"	14'-9"	447 sq.ft.
06- RECTANGLE	30'-9 1/2"	15'-11 1/2"	491 sq.ft.
07- RECTANGLE	19'-8"	5'-1 1/2"	101 sq.ft.
08- RECTANGLE	3'-6 1/2"	2'-5"	8 sq.ft.
			TOTAL 1ST FLOOR
			1,273 sq.ft.
09- RECTANGLE	6'-7"	2'- 5 1/2"	16 sq.ft.
10- RECTANGLE	12'-1"	14'-0"	168 sq.ft.
11- RECTANGLE	16'-4"	15'-4"	250 sq.ft.
12- RECTANGLE	12'-4 1/2"	1'-10"	23 sq.ft.
13- RECTANGLE	11'-1 1/2"	15'-6"	172 sq.ft.
14- RECTANGLE	3'-4 1/2"	3'-7 1/2"	12.2 sq.ft.
15- RECTANGLE	20'-5 1/2"	13'-5 1/2"	275 sq.ft.
16- RECTANGLE	15'-0"	5'-5"	81 sq.ft.
			TOTAL 2ND FLOOR
			998 sq.ft.
			TOTAL (EXCLUDED GARAGE
			2,271 sq.ft.

OOR AREA CALC	JLATION		
SECTION # (SHAPE)	SIDE A	SIDE B	FLOOR AREA OF SECTION FOOTPRINT
01- RECTANGLE	10'-10"	21'- 6 1/2"	233 sq.ft.
			TOTAL GARAGE
			233 sq.ft.
02- RECTANGLE	16'-9 1/2"	10'-2"	170 sq.ft.
03- RECTANGLE	6'-3 1/2"	7'-2"	45 sq.ft.
04- RECTANGLE	2'-5"	4'-4 1/2"	11 sq.ft.
05- RECTANGLE	30'-3 1/2"	14'-9"	447 sq.ft.
06- RECTANGLE	30'-9 1/2"	15'-11 1/2"	491 sq.ft.
07- RECTANGLE	19'-8"	5'-1 1/2"	101 sq.ft.
08- RECTANGLE	3'-6 1/2"	2'-5"	8 sq.ft.
			TOTAL 1ST FLOOR
			1,273 sq.ft.
09- RECTANGLE	6'-7"	2'- 5 1/2"	16 sq.ft.
10- RECTANGLE	12'-1"	14'-0"	168 sq.ft.
11- RECTANGLE	16'-4"	15'-4"	250 sq.ft.
12- RECTANGLE	12'-4 1/2"	1'-10"	23 sq.ft.
13- RECTANGLE	11'-1 1/2"	15'-6"	172 sq.ft.
14- RECTANGLE	3'-4 1/2"	3'-7 1/2"	12.2 sq.ft.
15- RECTANGLE	20'-5 1/2"	13'-5 1/2"	275 sq.ft.
16- RECTANGLE	15'-0"	5'-5"	81 sq.ft.
			TOTAL 2ND FLOOR
			998 sq.ft.
			TOTAL (EXCLUDED GARAGE)
			2,271 sq.ft.





acadia architecture


644 N. Santa Cruz Ave. Suite 6 Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com


ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN
MATERIAL APPEARING HEREIN
CONSTITUTE THE ORIGINAL,
UNPUBLISHED WORK OF
ACADIA-ARCHITECTURE AND THE
SAME MAY NOT BE DUPLICATED,
USED, OR DISCLOSED WITHOUT
THE WRITTEN CONSENT OF
ACADIA-ARCHITECTURE



A 1.2





GENERAL SHEET NOTES:

1. REFER TO MECHANICAL, ELECTRICAL, AND STRUCTURAL DRAWINGS FOR EXTENT OF MECHANICAL, ELECTRICAL, AND STRUCTURAL WORK.

2. ALL EXTERIOR STUD WALLS SHALL HAVE MIN. R-15 FOIL BACKED INSULATION.

3. REFER TO STRUCTURAL DRAWINGS FOR ALL FRAMING AND STRUCTURAL MEMBER SIZES.

4. PROVIDE FULLY TEMPERED GLAZING, LAMINATED SAFETY GLASS OR APPROVED PLASTIC IN SHOWERS OR BATHTUB ADJACENT WALL OPENINGS WITHIN 60 INCHES ABOVE A STANDING SURFACE AND DRAIN INLET.

5. DOORS AND PANELS OF SHOWER AND BATHTUB ENCLOSURES SHALL BE FULLY TEMPERED, LAMINATED SAFETY GLASS OR APPROVED PLASTIC.

6. PROVIDE TEMPERED GLAZING AT HAZARDOUS LOCATIONS, SUCH AS IN DOORS.

7. TUB-SHOWER COMBINATIONS SHALL BE PROVIDED WITH INDIVIDUAL CONTROL VALVES OF THE PRESSURE BALANCE OR THE THERMOSTATIC MIXING VALVE TYPE. PROVIDE MIXING VALVE FOR

8. PROVIDE PRESSURE RELIEF VALVE WITH DRAIN TO OUTSIDE AT WATER HEATER.

9. INSTALL WINDOWS PER MANUFACTURER'S RECOMMENDATIONS

10. DIMENSIONS ARE TO FINISH OF WALLS U.O.N.

11. MIN. JAMB AT DOORS TO BE 4"

DIMENSIONS NOTES

1-CONTRACTOR TO VERIFY ALL DIMENSIONS IN FIELD AND NOTIFY ARCHITECT OF ANY DISCREPANCY BEFORE ANY CONSTRUCTION

2- CONTRACTOR TO STAKE PROPERTY

LINES WITH SURVEYOR AND USE SETBACKS FOR ADDITION LAY-OUT

WATER HEATER NOTES:

WATER HEATERS REQUIRE TWO SEISMIC STRAPS; ONE LOCATED WITHIN THE TOP 1/3 OF THE WATER HEATER AND ONE AT THE BOTTOM 1/3. THE BOTTOM STRAP SHALL BE LOCATED AT LEAST 4" AWAY FROM THE HEATER CONTROLS. CPC

PLUMBING PLAN NOTES:

A) WATER CLOSETS SHALL HAVE AN AVERAGE WATER CONSUPTION OF NOT MORE THAN 1.28 GALLONS PER FLUSH. CPC 402.2C

B) SHOWER HEADS SHALL HAVE A WATER FLOW NOT TO EXCEED 2.5 GALLONS PER MINUTE. CPC

C) FAUCETS IN KITCHENS, WET BARS, LAVATORIES, LAUNDRY SINKS, ETC. SHALL HAVE A WATER FLOW NOT TO EXCEED 2.2 GALLONS PER MINUTE. CPC 402.1.2

EGRESS NOTES:

• EVERY SLEEPING ROOM SHALL HAVE AT LEAST ONE OPERABLE EMERGENCY ESCAPE AND RESCUE OPENING (R310.1)

a) MINIMUM NET CLEAR OPENABLE DIMENSION OF 24" IN HEIGHT (R310.1.2)

b) MINIMUM NET CLEAR OPENABLE DIMENSION OF 20" IN WIDTH (R310.1.3)

c) MINIMUM NET CLEAR OPENABLE DIMENSION OF 5.7 SQUARE FEET IN AREA. GRADE FLOOR OPENINGS SHALL HAVE A MINIMUM NET CLEAR OPENING OF 5 SQUARE FEET

d) OPENINGS SHALL HAVE A SILL HEIGHT OF NOT MORE THAN 44" MEASURED FROM THE FLOOR

STAIRWAY REQUIREMENT

A. STAIRWAYS SHALL NOT BE LESS THAN 36 INCHES IN CLEAR WIDTH ABOVE THE HANDRAILS. HANDRAIL PROJECTIONS ARE LIMITED TO NOT MORE THAN 4.5 INCHES ON EITHER SIDE OF THE STAIRWAY. (CRC Sec.R311.7.1)

B. HEADROOM SHALL NOT BE LESS THAN 6 FEET 8 INCHES MEASURED FROM THE SLOPED LINE ADJOINING THE TREAD NOSING. (CRC R311.7.2)

C. RISER HEIGHT SHALL NOT EXCEED 7 3/4 INCHES. THE GREATEST RISER HEIGHT WITHIN ANY FLIGHT OF STAIRS SHALL NOT EXCEED THE SMALLEST BY MORE THAN 3/8". (CRC Sec.R311.7.4.1).

D. TREAD DEPTH (MEASURED BETWEEN THE NOSING) SHALL BE AT LEAST 10 INCES. THE LARGEST TREAD DEPTH WIITHIN ANY FLIGHT OF STAIRS SHALL NOT EXCEED THE SMALLEST BY MORE THAN 3/8" (CRC Sec.R311.7.4.2)

E. NOSING NOT LESS THAN 0.75" BUT NOT MORE THAN 1.25" SHALL BE PROVIDED ON STAIRWAYS WITH SOLID RISERS IF THE TREAD DEPTH IS LESS THAN 11". THE RADIUS OF CURVATURE AT THE NOSING SHALL BE NO GREATER THAN 9/16 INCH. (CRC Sec.R311.7.4.3).

F. OPEN RISERS ARE PERMITTED, PROVIDED THAT THE OPENING BETWEEN TREADS DOES NOT PERMIT THE PASSAGE OF A 4- INCH DIAMETER SPHERE. THE OPENING BETWEEN ADJACENT TREADS IS NOT LIMITED ON STAIRS WITH A TOTAL RISE OF 30 INCHES OF LESS. (CRC Sec. R311.7.4.3)

GRAPHIC KEY:

EXISTING WALL TO REMAIN

NEW FRAMED EXTERIOR / INTERIOR WALL S.S.D.

FIRE RESISTIVE WALL CONSTRUCTION AT WALLS BETWEEN GARAGE AND LIVABLE SPACE:
MIN. 1/2" GYPSUM BOARD TYPE X OVER STUDS FROM CURB TO UNDERSIDE OF ROOF SHEATING APPLIED TO INTERIOR SIDE OF THE EXTERIOR WALLS







SID

Davide Giannella A.I.A



acadia architecture

644 N. Santa Cruz Ave. Suite Los Gatos, California 95030 T. 408-219-0601


dg@acadia-architecture.com **ACADIA-ARCHITECTURE**

All DRAWINGS AND WRITTEN MATERIAL APPEARING HEREIN CONSTITUTE THE ORIGINAL, UNPUBLISHED WORK OF ACADIA-ARCHITECTURE AND THE SAME MAY NOT BE DUPLICATED, USED, OR DISCLOSED WITHOUT THE WRITTEN CONSENT OF ACADIA-ARCHITECTURE

ALL RIGHTS RESERVED



A 2.0



GENERAL SHEET NOTES:

1. REFER TO MECHANICAL, ELECTRICAL, AND STRUCTURAL DRAWINGS FOR EXTENT OF MECHANICAL, ELECTRICAL, AND STRUCTURAL WORK.

2. ALL EXTERIOR STUD WALLS SHALL HAVE MIN. R-15 FOIL BACKED INSULATION.

3. REFER TO STRUCTURAL DRAWINGS FOR ALL FRAMING AND STRUCTURAL MEMBER SIZES.

4. PROVIDE FULLY TEMPERED GLAZING, LAMINATED SAFETY GLASS OR APPROVED PLASTIC IN SHOWERS OR BATHTUB ADJACENT WALL OPENINGS WITHIN 60 INCHES ABOVE A STANDING SURFACE AND DRAIN INLET.

5. DOORS AND PANELS OF SHOWER AND BATHTUB ENCLOSURES SHALL BE FULLY TEMPERED, LAMINATED SAFETY GLASS OR APPROVED PLASTIC.

6. PROVIDE TEMPERED GLAZING AT HAZARDOUS LOCATIONS, SUCH AS IN DOORS.

7. TUB-SHOWER COMBINATIONS SHALL BE PROVIDED WITH INDIVIDUAL CONTROL VALVES OF THE PRESSURE BALANCE OR THE THERMOSTATIC MIXING VALVE TYPE. PROVIDE MIXING VALVE FOR ALL TUB/SHOWERS

8. PROVIDE PRESSURE RELIEF VALVE WITH DRAIN TO OUTSIDE AT WATER HEATER.

- 9. INSTALL WINDOWS PER MANUFACTURER'S RECOMMENDATIONS
- 10. DIMENSIONS ARE TO FINISH OF WALLS U.O.N.
- 11. MIN. JAMB AT DOORS TO BE 4"

DIMENSIONS NOTES

1-CONTRACTOR TO VERIFY ALL DIMENSIONS IN FIELD AND NOTIFY ARCHITECT OF ANY DISCREPANCY BEFORE ANY CONSTRUCTION

2- CONTRACTOR TO STAKE PROPERTY

LINES WITH SURVEYOR AND USE SETBACKS FOR ADDITION LAY-OUT

WATER HEATER NOTES:

WATER HEATERS REQUIRE TWO SEISMIC STRAPS; ONE LOCATED WITHIN THE TOP 1/3 OF THE WATER HEATER AND ONE AT THE BOTTOM 1/3.
THE BOTTOM STRAP SHALL BE LOCATED AT LEAST 4" AWAY FROM THE HEATER CONTROLS. CPC

PLUMBING PLAN NOTES:

A) WATER CLOSETS SHALL HAVE AN AVERAGE WATER CONSUPTION OF NOT MORE THAN 1.28 GALLONS PER FLUSH. CPC 402.2C

B) SHOWER HEADS SHALL HAVE A WATER FLOW NOT TO EXCEED 2.5 GALLONS PER MINUTE. CPC

C) FAUCETS IN KITCHENS, WET BARS, LAVATORIES, LAUNDRY SINKS, ETC. SHALL HAVE A WATER FLOW NOT TO EXCEED 2.2 GALLONS PER MINUTE. CPC 402.1.2

EGRESS NOTES:

• EVERY SLEEPING ROOM SHALL HAVE AT LEAST ONE OPERABLE EMERGENCY ESCAPE AND RESCUE OPENING (R310.1)

a) MINIMUM NET CLEAR OPENABLE DIMENSION OF 24" IN HEIGHT (R310.1.2)

b) MINIMUM NET CLEAR OPENABLE DIMENSION OF 20" IN WIDTH (R310.1.3)

c) MINIMUM NET CLEAR OPENABLE DIMENSION OF 5.7 SQUARE FEET IN AREA.
GRADE FLOOR OPENINGS SHALL HAVE A MINIMUM NET CLEAR OPENING OF 5 SQUARE FEET

d) OPENINGS SHALL HAVE A SILL HEIGHT OF NOT MORE THAN 44" MEASURED FROM THE FLOOR

STAIRWAY REQUIREMENT

A. STAIRWAYS SHALL NOT BE LESS THAN 36 INCHES IN CLEAR WIDTH ABOVE THE HANDRAILS. HANDRAIL PROJECTIONS ARE LIMITED TO NOT MORE THAN 4.5 INCHES ON EITHER SIDE OF THE STAIRWAY. (CRC Sec.R311.7.1)

B. HEADROOM SHALL NOT BE LESS THAN 6 FEET 8 INCHES MEASURED FROM THE SLOPED LINE ADJOINING THE TREAD NOSING. (CRC R311.7.2)

C. RISER HEIGHT SHALL NOT EXCEED 7 3/4 INCHES. THE GREATEST RISER HEIGHT WITHIN ANY FLIGHT OF STAIRS SHALL NOT EXCEED THE SMALLEST BY MORE THAN 3/8". (CRC Sec.R311.7.4.1).

D. TREAD DEPTH (MEASURED BETWEEN THE NOSING) SHALL BE AT LEAST 10 INCES. THE LARGEST TREAD DEPTH WIITHIN ANY FLIGHT OF STAIRS SHALL NOT EXCEED THE SMALLEST BY MORE THAN 3/8" (CRC Sec.R311.7.4.2)

E. NOSING NOT LESS THAN 0.75" BUT NOT MORE THAN 1.25" SHALL BE PROVIDED ON STAIRWAYS WITH SOLID RISERS IF THE TREAD DEPTH IS LESS THAN 11". THE RADIUS OF CURVATURE AT THE NOSING SHALL BE NO GREATER THAN 9/16 INCH. (CRC Sec.R311.7.4.3).

F. OPEN RISERS ARE PERMITTED, PROVIDED THAT THE OPENING BETWEEN TREADS DOES NOT PERMIT THE PASSAGE OF A 4- INCH DIAMETER SPHERE. THE OPENING BETWEEN ADJACENT TREADS IS NOT LIMITED ON STAIRS WITH A TOTAL RISE OF 30 INCHES OF LESS. (CRC Sec. R311.7.4.3)

GRAPHIC KEY:

EXISTING WALL TO REMAIN

NEW FRAMED EXTERIOR / INTERIOR WALL S.S.D.

FIRE RESISTIVE WALL CONSTRUCTION
AT WALLS BETWEEN GARAGE AND LIVABLE SPACE:
MIN. 1/2" GYPSUM BOARD TYPE X OVER STUDS FROM CURB
TO UNDERSIDE OF ROOF SHEATING APPLIED TO INTERIOR
SIDE OF THE EXTERIOR WALLS







Revision

to CA

1A RESIDENCE

ng Ave. Palo Alto C

1832 Channi SECOI

n By DG ewed By DG

Davide Giannella A.I.A.



acadia architecture


644 N. Santa Cruz Ave. Suite 6 Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com

ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN
MATERIAL APPEARING HEREIN
CONSTITUTE THE ORIGINAL,
UNPUBLISHED WORK OF
ACADIA-ARCHITECTURE AND THE
SAME MAY NOT BE DUPLICATED,
USED, OR DISCLOSED WITHOUT
THE WRITTEN CONSENT OF
ACADIA-ARCHITECTURE



A 2.1



ESIDENC

JKNAMA KESIDI Channing Ave. Pal

1832 Ch

wn By DG iewed By DG

Davide Giannella A.I.A.



acadia architecture


644 N. Santa Cruz Ave. Suite 6 Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com


ACADIA-ARCHITECTURE ALL RIGHTS RESERVED


All DRAWINGS AND WRITTEN
MATERIAL APPEARING HEREIN
CONSTITUTE THE ORIGINAL,
UNPUBLISHED WORK OF
ACADIA-ARCHITECTURE AND THE
SAME MAY NOT BE DUPLICATED,
USED, OR DISCLOSED WITHOUT
THE WRITTEN CONSENT OF
ACADIA-ARCHITECTURE



A 2.2







Sheet Scale : AS NOTEDPURNAMA RESIDENCEDrawn By DG1832 Channing Ave. Palo Alto CAReviewed By DGRevision199/11/2015Proj. # EXTERIOR EL EVATIONS

Davide Giannella A.I.A.



acadia architecture


644 N. Santa Cruz Ave. Suite 6 Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com


ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN
MATERIAL APPEARING HEREIN
CONSTITUTE THE ORIGINAL,
UNPUBLISHED WORK OF
ACADIA-ARCHITECTURE AND THE
SAME MAY NOT BE DUPLICATED,
USED, OR DISCLOSED WITHOUT
THE WRITTEN CONSENT OF
ACADIA-ARCHITECTURE



A 3.0





SIDE WEST ELEVATION
Scale: 1/4" = 1'-0"

PURNAMA RESIDENCE 1832 Channing Ave. Palo Alto CA

Sheet Scale
Drawn By DC
Reviewed By
Pyreviewed By



acadia architecture

644 N. Santa Cruz Ave. Suite 6 Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com

ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN
MATERIAL APPEARING HEREIN
CONSTITUTE THE ORIGINAL,
UNPUBLISHED WORK OF
ACADIA-ARCHITECTURE AND THE
SAME MAY NOT BE DUPLICATED,
USED, OR DISCLOSED WITHOUT
THE WRITTEN CONSENT OF
ACADIA-ARCHITECTURE



A 3.1




Planning Segresheet A SITE Pussible Points Recommended A site	Project Name Rater Number Planning Scoresheet Yes a Tuf Shall Not Be Installed in Areas Less than 8 Feet Wide Install	Project State	This project is required to comply with the State California Green Building Code (T24 Part 11) and the City of Palo Alto's local amendments (PAMC 16.14). I, the <u>property owner</u> / legal representative, acknowledge and understand the requirements and penalties for noncompliance (\$50 per ton of waste not diverted from the landfill with a minimum of \$1000, and \$500 a day for noncompliance with the remaining green building measures). I am responsible for all activities performed by design team members, contractors and subcontractors in meeting the requirements.	
Protect Topscal and Minimize Disruption of Easting Plants & Trees 2	Yes S. Pant Shart's Trees 0 1 1 A A R	No	Signature Date Print Full Name Phone or Email	
Yes a Install Termite Shields & Separate All Exterior Wood-to-Concrete Connections 1 R R Pents Have Trunk, Base, or Stern Located All Losal 36 Inches from Foundation 1 R R Pents Available For Management Pents Available in Foundation 1 R R Pents Available Per Weeksitts C. LANDSC C. LANDSC Outher Proceedings of landscape area. (Projects with less than 15% of the following measures: Crit through Crit and Crit phint of the following measures: Crit through Crit and Crit phintograph Crit. Yes 1, Group Plants by Water Needs (Hydrozoning) 2 A A A R Pents Available Per Weeksitts Yes 2. Mulch All Planting Beds to the Greater of 3 Inches or Local Water Cortinance Requirement Total Provided Plants by Call-PC Are Planted 1 R Pents Available Per Weeksitts Yes 3. No Invasive Species Listed by Call-PC Are Planted 1 R Pents Available Per Weeksitts Yes 4. No Invasive Species Listed by Call-PC Are Planted 1 R Pents Available Per Weeksitts Yes 5. No Pint Species Will Require Shearing 1 R Pents Available Per Weeksitts Yes 6. No Pint Species Will Require Shearing 1 R Pents Available Per Weeksitts Yes 6. No Pint Species Will Require Shearing 1 R Pents Available Per Weeksitts Yes 6. No Pint Species Will Require Shearing 1 R Pents Available Per Weeksitts Yes 7. No Invasive Species Listed by Call-PC Are Planted 1 R Pents Available Per Weeksitts Yes 6. No Pint Species Will Require Shearing 1 R Pents Available Per Weeksitts Yes 7. No Invasive Species Listed by Call-PC Are Planted 1 R Pents Available Per Weeksitts Pents Available Per Weeksitts R Pents Available Per Week	3. Use Engineered Lumbor No a. Engineered Lumbor for Roof Rafters Ves b. Wood I-Joiste or Web Trusses for Floors Length and the Research of Pringer-Jointed Study for Vertical Applications O 1 1 R D D D D D D D D D D D D D D D D D	No a. Uso Central Core Plumbing 2. Water Efficient Fixtures Ves a. High Efficiency Showtheads \$2.0 Gottons Per Minute (gpm) at 80 pst, (Multiple showtheads shall not occeed maximum flow rates) (CALS-very-rocks if approachs) Yes b. High Efficiency Michinon Faucets \$1.5 gpm at 60 pst, (Multiple showtheads shall not occeed maximum flow rates) (CALS-very-rocks if approachs) Yes c. High Efficiency Michinon Faucets \$1.5 gpm at 60 pst, (CALS-very-rocks if approachs) Yes c. High Efficiency Total (Dust-Flush or \$1.25 gpm) (CALS-very-rocks if approachs) Yes 3. Install Only High Efficiency Total (Dust-Flush or \$1.25 Galloins Por plush (gpf)) (CALC-from code if application) Total Points Available in Plumbing = 12 12. Points Available Per Measure Yes 3. Design and Install HYAC System and Perform Diagnostic Testing a. Design and Install HYAC System to ACCA Manual J. D. and S Recommendations (CALG-very code if application) [This credit is a requirement associated with JH; EPA IAP] O Build it Green Green Point Rafed Single Family New Home Data Collection Form version 4.2 Page 3 of 9	RATER Acknowledgement The project will be verified by (choose only one): Build It Green City of Palo Alto Min. required points, greater of: 34 or 70	
Piroject Name Reter Name Reter Name Reter Name Pionality Scoresinges Pionality Scoresinges Yes b. Test Total Supply Air Flow Rates [1] In the created is a requirement associated with Jr. EPA IAP] [1] In screet is a requirement associated with Jr. EPA IAP] [1] In screet is a requirement associated with Jr. EPA IAP] [1] In screet is a requirement associated with Jr. EPA IAP] [2] In screen is a requirement associated with Jr. EPA IAP] [2] [3] In statist Ingle Refined is a requirement associated with Jr. EPA IAP] [3] In statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [3] In statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [4] In the statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [5] In the statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [6] In the statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [6] In the statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [6] In the statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Refined Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [7] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [8] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [8] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [8] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [8] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [8] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [8] [8] In the statist Ingle Reterming Zoned Hydronic Radiant Heating [8] [8] In the statist Ingl	Rater Number No b. House Passes Blower Door Test The credit is a requirement associated with J4: EPA IAP) No c. Blower Door Results are Max 2.5 ACH, for Unbalanced Systems (Supply of Exhaust) or Amax 1.0 ACH, for Balanced Systems (2 Table Pictus for J1b. and J1c.) Re TBD d. House Passes Combustion Safety Baskdraft Test 2. Requires: Building Performance Exceeds Title 24 (Minimum 15%) (Enter Inches Passes Combustion Safety Baskdraft Test TBD 3. Design and Build Near Zero Energy Homes (Enter Inches Inch	Project Name Rater Name Rater Name Plainting Scoresines The After installation of Finishes, Test of Indoor Air Shows Formstothydo Level - 27ppb Total Available Points in Finishes - 27 11 Points Available Per Measure Points Available Per Measure 1	I have reviewed the project plans and specifications, and they are in conformance with the GreenPoint Rated points claimed. I have reviewed and understand the after construction requirements below. Rater Signature Date YARMICA LEWNETI BIG-2009-245	
No c. Pressure Relieve the Ductwork System PTUS cords is a designment associated with J4: EPA IAP? Yos 6. Install High Efficiency HVAC Filter (MERV 61) (PTus cords is a requirement associated with J4: EPA IAP?) 7. No Fireplace OR Install Scaled Gas Fireplace(s) with Efficiency Rating > 60% using CSA Standards (PTus cords is a requirement associated with J4: EPA IAP) Yos 7. No Fireplace OR Install Scaled Gas Fireplace(s) with Efficiency Rating > 60% using CSA Standards (PTus cords is a requirement associated with J4: EPA IAP) Yes 3. Install ENERGY STAR Bathroom Fans on Timer or Humidistal (CAL Green code if 1 g.	No a. Energy Efficiency Program No (This credit is a requirement associated with J4: EPA IAP) No b. Renowable Energy Program with Min. 30% Better Than Tatle 24 (High Performing 0 1 A A A A	Yes 1. Install EMERGY STAR Dishwasher (Must Meet Current Specifications) Z	YARMUA UERA O NETSCAPE, NET Phone or Email SECTION TO BE COMPLETED AFTER CONSTRUCTION After construction is complete submit the following at the City Development Center	
Yes 1. Pre-Plumb for Solar Water Heating Yes 2. Install Wining Conduit for Future Photovolials Installation & Provide 20 0ft of South-Facing Roof 3. Offset Energy Consumption with Onsite Renewable Generation (Solar PV, Solar Thormal, Winin) Entr 1/ Italians (Solar PV, Solar Thormal, Winin) Total Available Ponts in Renewable Energy - 2 2 Points Available Por Measure J. BUILDINK 1. Building Envelope Diagnostic Evaluations a. Verify Quality of Insulation Installation & Thormal Byposs Checklist before Drywall ['This credit is a requirement associated with JA: EPA IAP] O Build II Green GreenPoint Rated Single Family New Home Data Collection Form version 4.2 Page 4 of 9 Page 4 of 9	7. Reduce Formaldehyde in Interior Finish - Meet Current CARB Altborne Total Control Measure (ATCM) for Composite Wood CARB Altborne Total Control Measure (ATCM) for Composite Wood PThis credit is a requirement associated with J4: EPA AP) 8. Reduce Formaldehyde in Interior Finish - Exceed Current CARB ATCM for Composite Wood Formaldehyde Limits Prior to Mandatory Compliance Dates TBD a. Doors (90% Minimum) Yes b. Cabinets & Counterlops (90% Minimum) Collision of Composite Wood Formaldehyde Limits Prior to Mandatory Compliance Dates TBD c. Interior Trim and Shelving (90% Minimum) O S S A A A A TBD c. Interior Trim and Shelving (90% Minimum) O S S A A A A TBD C. Interior Trim and Shelving (90% Minimum) O S S A A A A TBD C. Interior Trim and Shelving (90% Minimum) O Build It Green GreenPoint Rated Single Family New Home Data Collection Form version 4.2 Page 5 of 9	Yes This codd is a requirement associated with 3£ EPA IMP Yes b. Conduct Educational Walkfroughts (Prorequisite is N4a) This credit is a requirement 1	to schedule your final inspection: Construction debris receipts from an approved facility. If HERS testing was required per the homes energy report, attach the completed CF-4R ('s). If there were alterations during construction that impacted the energy report (i.e. R values, U factors, Equipment Types) rerun the report and attach it. If the project was City of Palo Alto verified, call for an on-site inspection at 329.2189.	
Record R	PERMITTISES PERMITTISES D. Structural Frame & Building Envelope 1. Design, Build and Maintain Structural Pest and Rot Controls 1. Design, Build and Maintain Structural Pest and Rot Controls 1. Design, Build and Maintain Structural Pest and Rot Controls 1. Design, Build and Maintain Structural Pest and Rot Controls 1. Design, Build and Maintain Structural Pest and Rot Controls 1. Design, Build and Maintain Structural Pest and Rot Controls 1. Design, Build and Maintain Structural Pest and Rot Controls 2. Locate All Wood (Siding, Trin, Structural) At Leost 12° Above Soil 3. All Wood Framing 3 Feet from the Foundation is Treated with Boreles 4. Design Structural Pest and Rot Controls 2. Des Mosture Resistant Materials in Wilder And Rot (Wood) 4. Des Mosture Rosistant Materials in Wilder And Rot (Wood) 4. Des Mosture Rosistant Materials in Wilder And Rot (Wood) 4. Des Mosture Rosistant Materials in Wilder And Rot (Wood) 5. Des Mosture Rosistant Materials in Wilder And Rot (Wood) 6. Plumbling 6. Plumbling 6. Des Wood (Siding, Trin, Structural) And Rot (Wood) 6. Install Printing (Includes Washing Machine at Minimum) 7. Des Wood (Siding, Trin, Structural) And Rot (Wood) 7. Des Wood (Siding, Trin, Structural) And Rot (Wood) 7. Des Wood (Siding, Trin, Structural) And Rot (Wood) 7. Des Wood (Siding, Trin, Structural) And Rot (Wood) 7. Des Wood (Siding, Trin, Structural) And Rot (Wood) 8. Install Drain Water Hoat Recovery System 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wood (Siding, Trin, Structural) And Rot (Wood) 9. Des Wo	Telegrating Scoresings Vos. 3. CA.Green 4.303.1 As an alternative to perscriptive compliance, a 20% reduction in baseline water use shall be demonstrated through calculation. Yos. 4. CA.Green 4.406.1 Jainis and spenings. Annular spaces around pipes, electric cables, candular, or other openings in pities at a startion wall staffled by profesciol. Yos. 5. CA.Green 4.505.2 The starting with Staffled at slab on grade foundations. Yes. 0. C.A.Green 4.505.2 Vapor retarder and capillary treats in its installed at slab on grade foundations. Yos. 7. CA.Green 4.505.2 The starting wall staffled at slab on grade foundations. Yes. 9. C.A.Green 4.505.2 Vapor retarder and capillary treats in its installed at slab on grade foundations. Yes. 9. C.A.Green 4.505.2 Vapor retarder and capillary treats in capillary treats. Yes. 1. CA.Green 4.505.2 Vapor retarder and capillary treats in staffled at slab on grade foundations. Yes. 9. C.A.Green 4.505.2 Vapor retarder and capillary treats in capillary treats. Yes. 1. CA.Green 4.505.2 Vapor retarder and capillary treats in Capillary treats. Yes. 1. CA.Green 4.505.2 Vapor retarder and capillary treats in Capillary treats. Yes. 2. CA.Green 4.505.2 Vapor retarder and capillary treats in Capillary treats. Yes. 3. CA.Green 4.505.2 Vapor retarder and capillary treats in Capillary treats. Yes. 3. CA.Green 4.505.2 Vapor retarder and capillary treats in Capillary treats. Yes. 3. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 4. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 4. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 4. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 4. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 4. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 5. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 6. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 7. CA.Green 4.505.2 Vapor retarder and capillary treats. Yes. 8. CA.Green 4.505.2 Vapor retarder and capillary t	I certify that: GreenPoint Rated inspections were performed throughout construction; The home has met the minimum required GreenPoint Rated points. Those required for landscaping may be excluded from this confirmation if verified within 6 months of final inspection; Through a combination of onsite inspections and confirmation from the Contractor there have been no alterations that impacted the energy report for the home, unless the new report is provided as an attachment; and that	J. F.
Recreational Interest Within 14 Anilo C. Install Traffe Calming Strategies (Minimum of Two): Designated Bicycle Lares are Present on Roadways; - Ten Foot Mohico Travel Lannes: - Street Crossings Closest to Site are Located Less Than 300 Feet Apart Street Have Rumbles Strips, Bluboust, Risased Crosswalks or Refuge Islands 5. Design for Safety & Social Gathering Yos A. All Home Front Entrances Have Views from the Inside to Outside Callers 1	No 2. Design HYAC System to Manual T for Register Design	Supplied has mit gail antifolious requirements It is a proposed to the control of the control o	Within six months (6) from the date of final inspection I will provide the City with the final BIG Certificate, final GreenPoint Rated Checklist and BIG Climate Calculator inputs.	VAMA RESIDEN CHANNING AV VALTO
RO I Route Downspout Through Permeable Landscape d. Use Non-Losching Roofing Materials No I I I I I I I I I I I I I I I I I I I	RESIDENTIAL	GreenPoint Rated Single Family New Home Data Collection Form version 4.2 Page 9 of 9 GREEN BUILDING APPL		PURN, 1832 C PALO
P4 Pay 05/07/2012	Title 24, Part 11, California Green Building Code (CALGreen) City of Palo Alto Green Building Ordinance 5107 (PAMC 16.14) City of Palo Alto Green Building Program and Resources Build It Green, GreenPoint Rated Guidelines and Checklists http://www.documents.dgs.ca http://www.cityofpaloalto.	hto.org/civica/filebank/blobdload.asp?BlobID=25863 Application: This plan sheet is for us 1,250sf.	9-2189 greenbuilding@cityofpaloalto.org se by residential new construction, additions and rebuilds over R1 Rev. 05/07/2012	UD"





WOOD TRELLIS





— BURNT RED STANDING SEAM METAL ROOFING RESIDENCE

Alto

Channing Ave. Palo

1832



acadia architecture

644 N. Santa Cruz Ave. Suite 6 Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com

ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN
MATERIAL APPEARING HEREIN
CONSTITUTE THE ORIGINAL,
UNPUBLISHED WORK OF
ACADIA-ARCHITECTURE AND THE
SAME MAY NOT BE DUPLICATED,
USED, OR DISCLOSED WITHOUT
THE WRITTEN CONSENT OF
ACADIA-ARCHITECTURE





MB


City of Palo Alto Tree Protection - It's Part of the Plan!

Make sure your crews and subs do the job right!

Fenced enclosures around trees are essential to protect them by keeping the foliage canopy and branching structure clear from contact by equipment, materials and activities, preserving roots and soil conditions in an intact and non-compacted state, and identifying the Tree Protection Zone (TPZ) in which no soil disturbance is permitted and activities are restricted, unless otherwise approved. An approved tree protection report must be added to this sheet when project activity occurs within the TPZ of a regulated tree. For detailed information on Palo Alto's regulated trees and protection during development, review the City Tree Technical Manual (TTM) found at www.cityofpaloalto.org/trees/.







* CIL	or PAIO	APPENDIX J PALO ALTO STREET TREE PROTECTION INSTRUCTIONSSECTION 31
31-1	Genera	
	а.	Tree protection has three primary functions, 1) to keep the foliage canopy and branching structure clear from contact by equipment, materials and activities; 2) to preserve roots and soil conditions in an intact and non-compacted state and 3) to identify the Tree Protection Zone (TPZ) in which no soil disturbance is permitted and activities are restricted, unless otherwise approved.
	b.	The Tree Protection Zone (TPZ) is a restricted area around the base of the tree with a radius of ten-times the diameter of the tree's trunk or ten feet; whichever is greater, enclosed by fencing.
31-2		ace Documents
	a.	Detail 605 – Illustration of situations described below.
	b.	Tree Technical Manual (TTM) Forms (http://www.cityofpaloalto.org/trees/) 1. Trenching Restriction Zones (TTM, Section 2.20(C))
		2. Arborist Reporting Protocol (TTM, Section 6.30)
		3. Site Plan Requirements (TTM, Section 6.35)
		4. Tree Disclosure Statement (TTM, Appendix J)
	c.	Street Tree Verification (STV) Form (http://www.cityofpaloalto.org/trees/forms)
31-3	Executi a.	Type I Tree Protection: The fence shall enclose the entire TPZ of the tree(s) to be protected throughout the life of the construction project. In some parking areas, if fencing is located on paving or concrete that will not be demolished, then the posts may be supported by an appropriate grade level concrete base, if approved by Public Works Operations.
	b.	Type II Tree Protection: For trees situated within a planting strip, only the planting strip and yard side of the TPZ shall be enclosed with the required chain link protective fencing in order to keep the sidewalk and street open for public use.
	c.	Type III Tree Protection: To be used only with approval of Public Works Operations. Trees situated in a tree well or sidewalk planter pit, shall be wrapped with 2-inches of orange plastic fencing from the ground to the first branch and overlaid with 2-inch thick wooden slats bound securely (slats shall not be allowed to dig into the bark). During installation of the plastic fencing, caution shall be used to avoid damaging any branches. Major limbs may also require plastic fencing as directed by the City Arborist.
	d.	Size, type and area to be fenced. All trees to be preserved shall be protected with six (6') foot high chain link fences. Fences are to be mounted on two-inch diameter galvanized iron posts, driven into the ground to a depth of at least 2-feet at no more than 10-foot spacing. Fencing shall extend to the outer branching, unless specifically approved on the STV Form.
	e.	'Warning' signs. A warning sign shall be weather proof and prominently displayed on each fence at 20-foot intervals. The sign shall be minimum 8.5-inches x 11-inches and clearly state in half inch tall letters: "WARNING - Tree Protection Zone - This fence shall not be removed and is subject to a fine according to PAMC Section 8.10.110."
	f.	Duration. Tree fencing shall be erected before demolition; grading or construction begins and remain in place until final inspection of the project, except for work specifically allowed in the TPZ. Work or soil disturbance in the TPZ requires approval by the project arborist or City Arborist (in the case of work around Street Trees). Excavations within the public right of way require a Street Work Permit from Public Works.
	g.	During construction
		 All neighbors' trees that overhang the project site shall be protected from impact of any kind. The applicant shall be responsible for the repair or replacement plus penalty of any publicly owned trees that are damaged during the course of construction, pursuant to Section 8.04.070 of the Palo Alto Municipal Code.
		 3. The following tree preservation measures apply to all trees to be retained: a. No storage of material, topsoil, vehicles or equipment shall be permitted within the TPZ. b. The ground under and around the tree canopy area shall not be altered. c. Trees to be retained shall be irrigated, aerated and maintained as necessary to ensure survival.
		END OF SECTION
		2004 Standard Drawings and Specifications
Street	Tree Verif	rication of Protection, PWE, Section 31 Revised 08/06

ALL CHECKE 1. Inspecting Month inspections	ence: the Palo Alto Tree Technical Manual is available at www.cityofpaloalto.org/environment/ DITEMS APPLY TO THIS PROJECT: etion of Protective Tree Fencing. For Public Trees, the Street Tree Verification Form shall be by the City Arborist. For Protected Trees, the project site arborist shall provide an initial day Tree Activity Report form with a photograph verifying that he has conducted a field tion of the trees and that the correct type of protective fencing is in place around the lated tree protection zone (TPZ) prior to issuance of a demolition, grading, or building permit.
ALL CHECKE 1. Inspecting Month inspections	DITEMS APPLY TO THIS PROJECT: ction of Protective Tree Fencing. For Public Trees, the Street Tree Verification Form shall be by the City Arborist. For Protected Trees, the project site arborist shall provide an initial ply Tree Activity Report form with a photograph verifying that he has conducted a field tion of the trees and that the correct type of protective fencing is in place around the lated tree protection zone (TPZ) prior to issuance of a demolition, grading, or building permit.
1. Inspecting Month inspections design	ction of Protective Tree Fencing. For Public Trees, the Street Tree Verification Form shall be by the City Arborist. For Protected Trees, the project site arborist shall provide an initial ally Tree Activity Report form with a photograph verifying that he has conducted a field tion of the trees and that the correct type of protective fencing is in place around the lated tree protection zone (TPZ) prior to issuance of a demolition, grading, or building permit.
	TM, Verification of Tree Protection, Section 1.39).
condu gradin	onstruction Meeting. Prior to commencement of construction, the applicant or contractor shall be a pre-construction meeting to discuss tree protection with the job site superintendent, g operators, project site arborist, City Arborist, and, if a city maintained irrigation system is ed, the Parks Manager (Contact 650-496-6962).
perfor TPZ to requir	etion of Rough Grading or Trenching. Contractor shall ensure the project site arborist ms an inspection during the course of rough grading or trenching adjacent to or within the ensure trees will not be injured by compaction, cut or fill, drainage and trenching, and if ed, inspect aeration systems, tree wells, drains and special paving. The contractor shall provide opect arborist at least 24 hours advance notice of such activity.
month immed Techn landso	bly Tree Activity Report Inspections. The project site arborist shall perform a minimum ly activity inspection to monitor and advise on conditions, tree health and retention or, diately if there are any revisions to the approved plans or protection measures. The Tree ical Manual Monthly Tree Activity Report format shall be used and sent to the Planning Dept ape review staff no later than 14 days after issuance of building permit date. Fax to (650) 329 (See TTM, Monthly Tree Activity Inspection Report, Addendum 11 & section 1.17).
requir	al activity within the Tree Protection Zone. Work in the TPZ area (see also #7 below) es the direct onsite supervision of the project arborist (see TTM, Trenching, Excavation & ment, Section 2.20 C).
final o on site Qualit constr verific	scape Architect Inspection. For discretionary development projects, prior to temporary or occupancy the applicant or contractor shall arrange for the Landscape Architect to perform an einspection of all plant stock, quality of the materials and planting (see TTM, Planting y, Section 5.20.1 A) and that the irrigation is functioning consistent with the approved action plans. The Planning Dept. landscape review staff shall be in receipt of written ration of Landscape Architect approval prior to scheduling the final inspection, unless wise approved.
7. List C	Other (please describe as called out in the site Tree Preservation Report, Sheet T-1, T-2, etc.)

City of Palo Alto Tree Department Public Works Operations PO Box 10250 Palo Alto, CA 9- 650/496-5953 FAX: 650/852-9 treeprotection@CityofPaloAlto.		94303 9289		rification of Tree Protection	
	ns: Complete upper portionent to Public Works Dept. F			form along with signed Tree	
APPLICATION DA	· -	abilo Work	TTOO Glan Will Inop	осос ана носту аррисана	
ADDRESS/LOCA TREES TO BE PF	TION OF STREET ROTECTED:				
APPLICANT'S NA	AME:				
APPLICANT'S A	DDRESS:				
APPLICANT'S TE & FAX NUMBERS					
This section to be	filled out by City Tree Staff	f			
address(es) a			YES 🗌	NO* □	
protected. The used is:	type of protection		* If NO,	go to #2 below	
Inspected by:					
Date of Inspect	ion:				
	are required:				
	were communicated .				
Subsequent Inspe	ction				
Street trees at about to be adequately p	ove address were found protected:	* If N	YES ☐ IO, indicate in "Notes	NO* " below the disposition of case.	
Inpsected by:					
Date of Inspection	n:				
site, condition and installed. Also not	treet trees by species, type of tree protection e if pictures were of sheet if necessary.				
Return approved S:PWD/OPS/Tree/DS/St.	sheet to Applicant for de	emolition or	building permit is	ssuance.	- 5

		-		Certified Arborist #WE- Contact Ce
N		ctivity Repo	rt- Construction	Site
Inspection Date:	Site address:	Contractor- Main Site Contact	#1: Job site superintend Company: Email:	lent
Inspection #	Palo Alto, CA	_ Information	Job site Office: Cell: Mail:	
		Also present:	:	
Distribution:	City of Palo Alto Others	Attn: Dave Dockter	Dave.dockter@cityofpald 650-329-2440	palto.org
c. Deten	et to verify that tree protect mine if field adjustments,			
a. Tree I b. Trenci 3. Action Item a. Tree I b. Root 2 c. Sched	Protection Fence (TPF) ne zone buffer material (woo ule sewer trench, foundat	number and date to eeds adjusting (tree ad chips) can be inst	be satisfied) and Date Due # x, x, x)	
a. Tree I b. Trenci 3. Action Item a. Tree I b. Root 2 c. Sched 4. Photograph	Protection Fences (TPF) a hing has/will occur has (list site-wide, by tree re- Protection Fence (TPF) ne cone buffer material (woo ule sewer trench, foundat s (use often)	number and date to eeds adjusting (tree ed chips) can be inst ion dig with	be satisfied) and Date Due # x, x, x)	
a. Tree I b. Trenci 3. Action Item a. Tree I b. Root 2 c. Sched 4. Photograph 5. Tree Locati	Protection Fences (TPF) a hing has/will occur as (list site-wide, by tree re Protection Fence (TPF) ne cone buffer material (woo ule sewer trench, foundat	number and date to eeds adjusting (tree ed chips) can be instituted in the ion dig with	be satisfied) and Date Due # x, x, x) talled next	
a. Tree I b. Trenci 3. Action Item a. Tree I b. Root 2 c. Sched 4. Photograph 5. Tree Locati	Protection Fences (TPF) a hing has/will occur as (list site-wide, by tree re Protection Fence (TPF) ne cone buffer material (woo ule sewer trench, foundat as (use often) on Map (mandatory 8.5 x	number and date to eeds adjusting (tree ed chips) can be instituted in the ion dig with	be satisfied) and Date Due # x, x, x) talled next	
a. Tree I b. Trenci 3. Action Item a. Tree I b. Root 2 c. Sched 4. Photograph 5. Tree Locati 6. Recommen	Protection Fences (TPF) a hing has/will occur as (list site-wide, by tree re Protection Fence (TPF) ne cone buffer material (woo ule sewer trench, foundat as (use often) on Map (mandatory 8.5 x	number and date to eeds adjusting (tree d chips) can be instion dig with (11 sheet)	be satisfied) and Date Due # x, x, x) talled next	
a. Tree I b. Trenci 3. Action Item a. Tree I b. Root 2 c. Sched 4. Photograph 5. Tree Locati 6. Recommen	Protection Fences (TPF) a hing has/will occur as (list site-wide, by tree re- protection Fence (TPF) ne cone buffer material (woo ule sewer trench, foundat as (use often) on Map (mandatory 8.5 x dations, notes or monitor	number and date to eeds adjusting (tree d chips) can be instion dig with (11 sheet)	be satisfied) and Date Due # x, x, x) talled next	
a. Tree I b. Trenci 3. Action Item a. Tree I b. Root 2 c. Sched 4. Photograph 5. Tree Locati 6. Recommen • 7. Past visits (Protection Fences (TPF) a hing has/will occur as (list site-wide, by tree re- protection Fence (TPF) ne cone buffer material (woo ule sewer trench, foundat as (use often) on Map (mandatory 8.5 x dations, notes or monitor list carry-over items satis	number and date to eeds adjusting (tree ed chips) can be instituted in ion dig with 11 sheet) items for project/st fied/still outstandin	be satisfied) and Date Due # x, x, x) talled next aff/schedule	

---WARNING---**Tree Protection Zone**

This fencing shall not be removed without City Arborist approval (650-496-5953)

Removal without permission is subject to a \$500 fine per day*

*Palo Alto Municipal Code Section 8.10.110 City of Palo Alto Tree Protection Instructions are located at http://www.city.palo-alto.ca.us/trees/technical-manual.htm

SPECIAL INSPECTIONS	PLANNING DEPARTMENT			
TREE PROTECTION INSPECTIONS MANDATORY				
PAMC 8.10 PROTECTED TREES. CONTRACTOR SHALL ENSURE PEREQUIRED TREE INSPECTION AND SITE MONITORING. PROVIDE VREPORTS TO THE PLANNING DEPARTMENT LANDSCAPE REVIEW BUILDING PERMIT ISSUANCE.	VRITTEN MONTHLY TREE ACTIVITY			
BUILDING PERMIT DATE:				
DATE OF 1ST TREE ACTIVITY REPORT:				
CITY STAFF:				
REPORTING DETAILS OF THE MONTHLY TREE ACTIVITY REPORT VERIFY THAT ALL TREE PROTECTION MEASURES ARE IMPLIMENT ACTIVITY, SCHEDULED OR UNSCHEDULED, WITHIN A TREE PRO IS SUBJECT TO VIOLATION OF PAMC 8.10.080. REFERENCE:	TED AND WILL INCLUDE ALL CONTRACTOR ITECTION ROOT ZONE. NON-COMPLIANCE			

Apply Tree Protection Report on sheet(s) T-2

Use addtional "T" sheets as needed

Project

T-1



All other tree-related reports shall be added to the space provided on this sheet (adding as needed) Include this sheet(s) on Project Sheet Index or Legend Page.

A copy of T-1 can be downloaded at http://www.cityofpaloalto.org/civica/filebank/blobdload.asp?BlobID=6460 Special Tree Protection Instruction Sheet City of Palo Alto



T-1

ENC SID



acadia architecture

644 N. Santa Cruz Ave. Suite Los Gatos, California 95030 T. 408-219-0601 dg@acadia-architecture.com

ACADIA-ARCHITECTURE ALL RIGHTS RESERVED

All DRAWINGS AND WRITTEN MATERIAL APPEARING HEREIN CONSTITUTE THE ORIGINAL UNPUBLISHED WORK OF ACADIA-ARCHITECTURE AND T SAME MAY NOT BE DUPLICATED USED, OR DISCLOSED WITHOUT

THE WRITTEN CONSENT OF

ACADIA-ARCHITECTURE



T-1