

**Water Quality and Streamflow Monitoring
of San Francisquito and Los Trancos
Creeks at Piers Lane, and Bear Creek at
Sand Hill Road, Water Year 2008,
Long-term Monitoring and Assessment
Program San Mateo and Santa Clara
Counties, California**

Report prepared for:

Stanford University, Utilities Division
Jasper Ridge Biological Preserve

Prepared by:

Jonathan Owens
Chris White
John Gartner
Travis Baggett
Barry Hecht

Balance Hydrologics, Inc.

March 2009


A report prepared for:

**Stanford University
Utilities Division**
327 Bonair Siding, 2nd Floor
Stanford, California 94305-7270
Attention: Marty Laporte
(650) 725-7864

**Jasper Ridge Biological Preserve
Stanford University**
Gilbert 109
Stanford, California 94305-5020
Attention: Philippe Cohen
(650) 723-1589

Water Quality and Streamflow Monitoring of San Francisquito and Los Trancos Creeks at Piers Lane, and Bear Creek at Sand Hill Road, Water Year 2008, Long-term Monitoring and Assessment Program, San Mateo and Santa Clara Counties, California


© 2009 Balance Hydrologics, Inc. Project Assignments: 202018 & 202094



Jonathan Owens
Senior Hydrologist




Chris White
Senior Water Quality Specialist





John Gartner
Hydrologist



Travis Baggett
Hydrologist



Barry Hecht, CEG, CHg
Hydrologist / Geomorphologist



**Balance
Hydrologics, Inc.®**

800 Bancroft Avenue
Berkeley, California 94710
510-704-1000
office@balancehydro.com

March 27, 2009

TABLE OF CONTENTS

SUMMARY AND CONCLUSIONS	1
1. INTRODUCTION	3
2. BACKGROUND.....	5
2.1 LOCAL INFLUENCES ON WATER QUALITY	5
2.2 RELATED WATER QUALITY STUDIES IN THE WATERSHED.....	6
3. STATION LOCATIONS	8
3.1 BEAR CREEK SUB-WATERSHED STATION.....	8
3.2 PIERS LANE STATIONS	9
3.3 OTHER STATIONS IN THE WATERSHED.....	10
3.3.1 <i>Los Trancos Creek at Arastradero Road</i>	10
3.3.2 <i>Searsville sub-watershed stations</i>	10
3.3.3 <i>U.S. Geological Survey station on San Francisquito Creek</i>	10
4. HYDROLOGIC SUMMARY, WATER YEAR 2008.....	11
4.1 NARRATIVE SUMMARY	11
4.2 PRECIPITATION	12
4.3 RETURN PERIOD OF PEAK FLOWS	12
4.4 UNEXPLAINED FLOW SURGES	12
4.5 CREATING A RECORD OF STREAMFLOW	13
4.5.1 <i>Developing a record of water levels</i>	13
4.5.2 <i>Computing flows</i>	14
5. WATER QUALITY SAMPLING APPROACH.....	15
5.1 FIELD MEASUREMENTS AND LABORATORY ANALYSES	15
5.2 EXCEPTIONS AND DEVIATIONS FROM PROPOSED METHODS	16
6. RESULTS AND DISCUSSION OF WATER QUALITY SAMPLING.....	17
6.1 SPECIFIC CONDUCTANCE	17
6.2 WATER TEMPERATURE	17
6.2.1 <i>Water temperature affects fish</i>	18
6.2.2 <i>Temperature monitoring probes</i>	18
6.2.3 <i>Temperature differences between creeks</i>	18
6.3 pH.....	18
6.4 DISSOLVED OXYGEN	19
6.5 SEDIMENT	20
6.5.1 <i>Suspended sediment</i>	21
6.5.2 <i>Bedload sediment</i>	21
6.5.3 <i>Sediment discussion</i>	22
7. FUTURE MONITORING AND RECOMMENDATIONS	24
8. LIMITATIONS.....	25
9. ACKNOWLEDGEMENTS	26
10. REFERENCES	27

LIST OF FORMS

- Form 1. Annual hydrologic record for Bear Creek at Sand Hill Road, water year 2008
- Form 2. Annual hydrologic record for Los Trancos Creek at Piers Lane, water year 2008
- Form 3. Annual hydrologic record for San Francisquito Creek at Piers Lane, water year 2008
- Form 4. Sediment-discharge record for Bear Creek at Sand Hill Road, water year 2008
- Form 5. Sediment-discharge record for Los Trancos Creek at Piers Lane, water year 2008
- Form 6. Sediment-discharge record for San Francisquito Creek at Piers Lane, water year 2008

LIST OF TABLES

- Table 1. Station observer log for Bear Creek at Sand Hill Road, water year 2008
- Table 2. Station observer log for San Francisquito Creek at Piers Lane, water year 2008
- Table 3. Station observer log for Los Trancos Creek at Piers Lane, water year 2008
- Table 4. Hydrologic summary for the period of record, Bear Creek, Los Trancos Creek and San Francisquito Creek
- Table 5. Measurements and calculations of sediment transport, Bear Creek at Sand Hill Road, water year 2008
- Table 6. Sediment-discharge measurements and calculations, San Francisquito Creek and Los Trancos Creek at Piers Lane, water year 2008

LIST OF FIGURES

- Figure 1. Site location and watershed map
- Figure 2. Daily flow hydrographs for San Francisquito, Los Trancos and Bear Creeks, water year 2008
- Figure 3. Daily flow hydrograph for Bear Creek at Sand Hill Road, water year 2008
- Figure 4. Daily flow hydrograph for San Francisquito Creek at Piers Lane, water year 2008
- Figure 5. Daily flow hydrograph for Los Trancos Creek at Piers Lane, water year 2008
- Figure 6. Unit flow hydrographs for San Francisquito, Los Trancos and Bear Creeks, water year 2008
- Figure 7. Cumulative 15-minute precipitation record at Bear Creek at Sand Hill Road, and San Francisquito Creek at Piers Lane, water year 2008
- Figure 8. Specific conductance measurements, Los Trancos Creek at Piers Lane, water years 2002 to 2008
- Figure 9. Specific conductance measurements, Bear Creek at Sand Hill Road, water years 2004 to 2008
- Figure 10. Specific conductance measurements, San Francisquito Creek at Piers Lane, water years 2002 to 2008
- Figure 11. Daily water temperature record for San Francisquito Creek at Piers Lane, water year 2008
- Figure 12. Daily water temperature record for Los Trancos Creek at Piers Lane, water year 2008
- Figure 13. Daily water temperature record for Bear Creek at Sand Hill Road, water year 2008
- Figure 14. pH measurements in San Francisquito, Los Trancos and Bear Creeks, water year 2008
- Figure 15. Dissolved oxygen concentrations in Bear Creek at Sand Hill Road, water year 2008
- Figure 16. Dissolved oxygen concentrations in Los Trancos Creek at Piers Lane, water year 2008
- Figure 17. Dissolved oxygen concentrations in San Francisquito Creek at Piers Lane, water year 2008

LIST OF FIGURES (CONTINUED)

- Figure 18. Sediment measurements and rating curves for the Piers Lane stations, water year 2008
- Figure 19. Sediment measurements and rating curves for Bear Creek at Sand Hill Road, water years 1998 to 2008

APPENDICES

- Appendix A. Laboratory results and chain of custody forms

SUMMARY AND CONCLUSIONS

San Francisquito Creek is currently listed by the California State Water Resources Control Board as being impaired by sediment and by the organophosphate pesticide, diazinon. Water quality in the creek is of particular concern because the creek is habitat for steelhead trout, a federally-listed threatened species. This study reports results of water year 2008 stream gaging and water quality sampling conducted as part of the Long-Term Monitoring and Assessment Program (LTMAP), a water-quality sampling program sponsored by Stanford University and the City of Palo Alto. Water year 2008 was the seventh year of monitoring at the Los Trancos Creek and San Francisquito Creek stations at Piers Lane, and the fifth year of monitoring at the Bear Creek at Sand Hill Road station. Due to budget constraints, only flow and sediment were monitored at Bear Creek beginning in water year 2007, and at the Piers Lane stations beginning in water year 2008. Measurements and observations at all three stations are continuing during water year 2009, though on a limited scale.

Since fall 2001, Balance Hydrologics, Inc. has operated for LTMAP two automated water-quality sampling stations on San Francisquito Creek and Los Trancos Creek at Piers Lane, just above their confluence. In fall 2003, Kinnetic Labs (Santa Cruz) installed another automated sampling station, located on Bear Creek at Sand Hill Road, along the northern border of the Jasper Ridge Biological Preserve. The station, which is now also operated by Balance Hydrologics, is configured similarly to the other stations with a datalogger, several probes, and a programmable pumping unit. As in previous years, the electronic records were combined with manual measurements to create flow records for each stream. Measurements of temperature, specific conductance, dissolved oxygen and pH were made manually. Suspended-sediment samples were collected as grab samples during and between storms and used to estimate annual suspended-sediment yields. Our conclusions are presented below, together with citations to the relevant text subsections, tables and figures:

1. Rainfall and streamflow totals for water year 2008 were below average. Rainfall was approximately 82 percent of the long-term average at the Bear Creek station and 92 percent of the long-term average at the Piers Lane stations. Peak streamflow was slightly above average; based on USGS provisional streamflow data for San Francisquito Creek, the peak flow for the year corresponds to about a 2.5-year recurrence-interval flood, equivalent to a 40.5 percent chance of being exceeded in any year. (*Sections 4.1 to 4.3; Table 4; Figures 2 to 5*)

2. Specific conductance values (*Section 6.1; Tables 1 to 3; Figures 8 to 10*) and pH values (*Section 6.3; Tables 1 to 3; Figure 14*) in all three streams were within the range of previous sampling results during water year 2008.
3. Dissolved oxygen concentrations (*Section 6.4; Tables 1 to 3; Figures 15 to 17*) were occasionally low – particularly in San Francisquito Creek in late summer or fall – a condition which may prove limiting for certain biota. This is consistent with previous years.
4. Dry-season water temperatures remained below lethal levels and below temperatures recorded in 2006 and other years, despite low baseflows and discontinuous pools in some upstream reaches. Low baseflows have a higher potential for high stream temperatures and, therefore, a greater impact on steelhead and other aquatic biota, especially if pools become discontinuous (*Sections 4.4 and 6.2; Tables 1 to 3; Figures 11 to 13*).
5. Fluctuations in flow and specific conductance during baseflow periods were most noticeable at the Bear Creek station, but also propagated downstream to San Francisquito Creek at Piers Lane. In addition, our records show multiple and various types of flow alterations in Los Trancos Creek. Upstream diversions and other flow alterations may affect baseflows and, therefore, aquatic habitat. Besides the volumetric changes to flow, water quality may also be altered by the apparent additions to creek flow (*Sections 4.4; Figures 3, 6, and 11 to 13*).
6. Even though water year 2008 was dry in terms of total flow, peak flows were moderately large. Therefore, roughly average or slightly below average amounts of sediment were discharged (*Section 6.5.3; Table 4; Figures 18 and 19*).

1. INTRODUCTION

This report presents the results of surface-water monitoring in the San Francisquito Creek watershed by Balance Hydrologics, Inc. (“Balance”), on behalf of the Stanford University Utilities Division, Jasper Ridge Biological Preserve, Stanford Management Company, SLAC National Accelerator Laboratory (all, “Stanford”) and the City of Palo Alto. Stanford is a participant in the San Francisquito Watershed Council, which is managing the Long-Term Monitoring and Assessment Program (LTMAP). The LTMAP was originally created by a subcommittee of the San Francisquito Creek Coordinated Resource Management and Planning (CRMP) Steering Committee, the group now known as the San Francisquito Watershed Council. The LTMAP was established primarily to monitor and assess current (i.e., baseline) conditions, analyze trends, and evaluate watershed management. Three LTMAP monitoring stations in the lower San Francisquito Creek watershed have been monitored since fall 2001 (water year 2002¹); monitoring at a fourth station higher in the watershed began in fall 2003.

The San Francisquito Creek watershed is located on the San Francisco Peninsula, and includes the northwestern portion of Santa Clara County and the southeastern portion of San Mateo County (Figure 1). Los Trancos Creek and (below their confluence) San Francisquito Creek form the boundary between the two counties. The watershed encompasses approximately 45 square miles, of which about 37 square miles lie upstream from the two Piers Lane stations, and includes a wide diversity of urbanized, rural and natural habitats. The 11.7-square mile Bear Creek sub-watershed encompasses the northwestern headwaters of San Francisquito Creek, covering approximately 25 percent of its watershed. Los Trancos Creek has a sub-watershed area of 7.8 square miles.

The first three LTMAP automated sampling stations were installed in fall 2001. The City of Palo Alto Regional Water Quality Control Plant staff are operating the lowermost station on San Francisquito Creek at Newell Road, a short distance upstream of Highway 101 and near the head of tidewater. Balance staff are operating the other two stations, on San Francisquito Creek and Los Trancos Creek at Piers Lane, a short distance downstream (north) of Interstate 280 and immediately upstream of the confluence of the two creeks. A fourth LTMAP station was

¹ Most hydrologic and geomorphic monitoring occurs for a period defined as a water year, which begins on October 1 and ends on September 30 of the named year. For example, water year 2007 (WY2007) began on Oct. 1, 2006 and concluded on September 30, 2007.

installed on Bear Creek at Sand Hill Road in fall 2003, reoccupying a site previously gaged by Balance staff. This station, which is also operated by Balance, is about 2.5 miles upstream from Piers Lane.

Data and findings from the initial two years of monitoring the Piers Lane stations are presented in the prior annual monitoring reports (Owens and others, 2003; Owens and others, 2004). To better integrate findings from the three stations currently monitored by Balance staff, results were summarized in a single report beginning with water year 2004, the third year of monitoring the two Piers Lane stations and the initial year of monitoring the Bear Creek at Sand Hill Road station (Owens and others, 2005) and continuing in water year 2005 (Owens and others, 2006), water year 2006 (Owens and others, 2007) and water year 2007 (Owens and others, 2008). This report similarly presents results of water year 2008 monitoring at all three stations operated by Balance. Measurements and observations will continue at all three stations during water year 2009 (WY2009), though on a limited scale.

2. BACKGROUND

Surface-water monitoring for this project is being implemented to assess known and potential pollutant concentrations as part of the Long-Term Monitoring and Assessment Program (LTMAP). The LTMAP was originally created by a subcommittee of the San Francisquito Creek Coordinated Resource Management and Planning (CRMP) Steering Committee, the group now known as the San Francisquito Watershed Council. The goals of the LTMAP are to provide a comprehensive framework for organizing and coordinating monitoring and assessment activities in the San Francisquito Creek watershed.

As part of the LTMAP, surface water data are being collected for use in describing constituents which might adversely affect water quality in the watershed, under storm runoff and low-flow conditions, in major part as they affect the full range of steelhead life stages. To assist the LTMAP in one of its objectives, Balance was asked to:

1. Identify which contaminants or sets of contaminants are present in San Francisquito Creek, Los Trancos Creek and Bear Creek, and to prioritize analyses for more detailed study in future years;
2. Assess if a relationship exists between the presence, absence or concentration of contaminants and streamflow; and
3. Evaluate the amount of suspended sediment and bedload being transported by the three streams and compare them to results from other locations in the watershed also monitored during this water year for other projects.

2.1 Local Influences on Water Quality

Restoration of habitat for steelhead -- a federally-listed threatened species greatly valued by the watershed community at large -- in the San Francisquito Creek drainage has been the focus of substantial efforts over the past ten years. Technical professionals and knowledgeable residents with experience in these streams suspect that water quality may be a significant constraint to the size and robustness of the steelhead population in San Francisquito Creek and its tributaries. Steelhead are anadromous² salmonids which spawn and rear throughout the free-flowing

² Migrates downstream to the ocean as a juvenile and returns upstream to fresh water to spawn.

headwaters of the San Francisquito Creek watershed. Water-quality impairment may likely affect other sensitive local species or possibly other beneficial uses as well.

The principal sources of potential concern include:

- horses and perhaps other livestock, particularly those boarded on land adjacent to the stream channels of San Francisquito Creek and its tributaries and/or using the stream or riparian buffer areas;
- septic systems, or other on-site wastewater-treatment units;
- urban runoff, including road and highway surface runoff, which may contribute nutrients and other constituents, such as heavy metals;
- pulses of water which have been repeatedly observed and documented in the streams at low flow, that may originate from human-managed sources, perhaps from flushing of swimming pools and other chlorinated ponds; and
- common garden, orchard and lawn or turf chemicals (i.e., fertilizers, pesticides).

Urban runoff and animal wastes from horses and other domesticated species, when washed into the creeks of the watershed, may be acutely toxic to steelhead and other fish or aquatic species. Chronic toxicity and/or indirect effects of these loadings may also counteract sustained regional efforts to improve and restore populations of steelhead. Each of the other sources listed above can also have chronic or acute toxicity.

The quantity of baseflow is also an important factor in maintaining habitat quality. Too little water in the creeks during the spring and summer can impede out-migration of year-old fish and affect summer survival of newly hatched “young-of-the-year” as well as year-old juveniles. Insufficient baseflow also magnifies the effects of introduced pollutants by reducing the amount of dilution available to decrease pollutant concentrations and at very low flows can lead to impaired conditions such as local increases in temperature or decreases in dissolved oxygen.

2.2 Related Water Quality Studies in the Watershed

We know of only one recent sub-watershed-scale investigation of water quality. As part of a grant from the Packard Foundation, the San Francisquito Watershed Council asked Balance to conduct a three-year water quality study in the Bear Creek portion of the larger watershed during water years 2000 through 2002. Balance has reported the results of the first two years of

monitoring (Owens and others, 2001; 2002). Both published and unpublished data from the Bear Creek study are used in this report as a basis for comparison. The Bear Creek watershed encompasses the northwestern headwaters of San Francisquito Creek, as shown in Figure 1. Thus, water-quality problems in the Bear Creek watershed can directly affect nearly all other spawning and rearing areas in the San Francisquito Creek watershed. Conversely, measures which control causes of toxicity to fish in the Bear Creek system will benefit nearly the entire local steelhead population, as well as other species in the San Francisquito Creek watershed. Knowledge of natural and anthropogenic factors affecting water quality in Bear Creek can help in planning and assessing water quality elsewhere in the watershed.

3. STATION LOCATIONS

3.1 Bear Creek Sub-watershed Station

The Bear Creek at Sand Hill Road station (designated as BCSH) is located on the northern border of the Jasper Ridge Biological Preserve (Figure 1), approximately 2.5 miles upstream of the San Francisquito Creek at Piers Lane station. Balance has periodically monitored streamflow and water-quality constituents at this site, which receives flows from almost one-half of the San Francisquito Creek watershed above Piers Lane, since the spring of 1997. Prior to the current study, the most complete sets of data were compiled during water years 2000 to 2002, when this station was one of eight stations in the watershed regularly monitored on behalf of the San Francisquito Watershed Council (see Section 2.2 above). Balance continued to operate the gaging station during water year 2003 but only minimal water quality measurements were made that year.

Through the combined efforts of Stanford Management Co., SLAC National Accelerator Laboratory, and the Jasper Ridge Biological Preserve, this location became the fourth station in the LTMAP monitoring network. In fall 2003 (WY2004), Kinnetic Laboratories, Inc. (Santa Cruz) installed new monitoring equipment on the left bank of Bear Creek, about 200 feet downstream from Sand Hill Road and only a short distance from the previous gaging location. The instream portion of this installation was severely damaged by the storm that began on Dec. 31, 2005. Temporary probes were installed one week later and permanent replacement of the instream components occurred in May 2006, with the assistance of Kinnetic Laboratories, Inc.

The station is equipped with a tipping-bucket rain gauge, a streamside staff plate, a datalogger and automated sampler pumping unit housed within an enclosure, and several water-quality probes. Water level, water temperature, specific conductance (an index of salinity), dissolved oxygen, and pH are continuously monitored. Water levels are measured using pressure transducers. Manual measurements of water levels at a staff plate, streamflow and water quality parameters are made at regular intervals to calibrate the electronic record. The station is connected to a land-line telephone so that real-time data can be monitored over the Internet. The automated sampler is designed to collect aliquots over a specified period into a composite sample bottle kept chilled in an ice bath. Following sampling events, sub-samples of the mixed composite sample are poured into prepared sample bottles for laboratory analysis of individual constituents.

3.2 Piers Lane Stations

The other two LTMAP stations discussed in this report³ are located on Los Trancos Creek and San Francisquito Creek, just upstream from their confluence, where Piers Lane crosses both creeks (Figure 1). The stations are within 100 yards of each other and only a short distance downstream (north) of Interstate 280. The stations were installed in fall 2001 by staff of Kinnetic Laboratories, Inc. and Larry Walker Associates (Davis) under contract to the City of Palo Alto. The station on San Francisquito Creek is equipped with a tipping-bucket rain gauge. From installation through fall 2005, water levels at both stations were measured by an ultrasonic sonar transponder mounted on the bridge above the creek at each site. Following failure of the transponder at the San Francisquito Creek station in November 2005, Balance installed a set of temporary probes and worked with City of Palo Alto Regional Water Quality Control Plant and Stanford staff to develop a repair plan that would also address maintenance problems at both Piers Lane stations, as detailed in previous monitoring reports. To improve reliability, a datalogger and pressure transducers were installed at the San Francisquito Creek station in February 2006, and the specific conductance probe was replaced with one of a different brand. Both stations remain powered by batteries, but solar panels were installed at each site to reduce or eliminate intermittent problems with battery failure that have resulted in occasional loss of monitoring data. The cable to the rain gauge was sheathed in conduit and buried to reduce chances of rodent damage. Sampling tubes at both stations were replaced and a second conduit was installed between the enclosures and the streams to carry the probe cables and reduce constriction in the original conduits. Otherwise, each station is equipped with the same instrumentation described above for the Bear Creek station and is monitored using the same protocols. Cell phone telemetry was attempted in the past but found to drain the batteries too quickly to make the data available in real-time.⁴

Balance initiated operation of the newly-installed Piers Lane stations, designated as San Francisquito Creek at Piers Lane (SFPL) and Los Trancos Creek at Piers Lane (LTPL), at the start of water year 2002. For a number of reasons detailed in the first-year (WY2002) monitoring report (Owens and others, 2003), only a limited number of samples were collected during the

³ The fourth LTMAP station, on San Francisquito Creek at Newell Road, a short distance upstream of Highway 101, has been operated by staff of the City of Palo Alto Regional Water Quality Control Plant since it was installed in fall 2001. Monitoring at this site is coordinated with activities at the upstream stations but results are interpreted by City staff and reported under separate cover.

⁴ Connection to a land-line telephone would decrease obstacles to real-time data availability but is reportedly not feasible at this time.

first year of operation. Monitoring during water years 2003 to 2007 more closely followed the envisioned sampling sequence.

3.3 Other Stations in the Watershed

As part of a series of cooperating projects, Balance also monitored a number of locations in the San Francisquito Creek watershed upstream of Piers Lane during water year 2008 (Figure 1). The main focus was on monitoring streamflow and sediment discharge. Data from some of these other stations are used in this report for comparison to the data collected at the Piers Lane stations. Comparison of flow records among stations helps to verify the gaging data and describe and document differences in hydrologic responses to rainfall. These differences are proving larger than expected, such as very low baseflows on West Union Creek, or flashy storm peaks on Dry Creek, and may prove in and of themselves to be of significance to stream management, including steelhead restoration. Selected stations are described below.

3.3.1 Los Trancos Creek at Arastradero Road

Balance operates another station on Los Trancos Creek (LTAA) about 1.8 miles upstream of Piers Lane on behalf of Stanford University Utilities Division. This upstream station has been in operation since November 1994. Suspended-sediment and bedload discharge are also collected at this site. The watershed area upstream of this station is 5.3 square miles.

3.3.2 Searsville sub-watershed stations

Balance operated gages at Searsville Dam and upstream from Searsville Lake on Corte Madera Creek at Westridge Drive during water year 2008. Data collection from the Searsville sub-watershed stations focuses on sediment transport. Searsville and Corte Madera Creek flow data were considered during data analysis and in this report where such comparisons were useful.

3.3.3 U.S. Geological Survey station on San Francisquito Creek

USGS stream gage #1164500 (San Francisquito Creek at Stanford University) is located approximately 0.5 miles downstream from Piers Lane. This station was originally established in 1931 and has maintained a continuous record of flow since 1954. USGS staff regularly collected suspended-sediment (but not bedload sediment) data at this station from the mid-1960s to early 1970s (Brown and Jackson, 1973).

4. HYDROLOGIC SUMMARY, WATER YEAR 2008

Observations and measurements from our water year 2008 site visits are documented in Table 1 (Bear Creek), Table 2 (Los Trancos Creek) and Table 3 (San Francisquito Creek). Annual hydrologic summaries for each of the three creeks are presented in Forms 1 to 3. Table 4 is a hydrologic summary for all three creeks over the period of record. For Bear Creek, the summary includes gaging results from the earlier three-year water quality study (water years 2000 to 2002).

Daily flow hydrographs for the three creeks are plotted on the same graph in Figure 2, and for individual creeks in Figures 3 to 5. Figure 6 shows the unit flow hydrograph for each creek. “Unit flow”, calculated by dividing the mean daily flow by the watershed area, allows comparison of the response to rainfall among different watersheds. In general, the magnitude of streamflow is governed by the size of the watershed, so that a larger watershed produces higher flows. However, differences among streams in wet- and dry-season baseflows also reflect variations in the geology, topography and management of diversions within their watersheds.

4.1 Narrative Summary

In general, water year 2008 was a dry year in terms of total rainfall (Figure 7) and total flow, but peak flows (Figure 2) were about normal. The water year began with very low baseflow in fall 2007 due to below-average rainfall the previous year. Light rains fell during October, November, and December of 2007, which gradually elevated baseflow. The two largest events of the season were strong, 12-hour storms of wind and rain on January 4 and January 25, 2008. Several moderate rains occurred during February but rainfall virtually ceased after the last significant storm event of water year 2008, on February 24, 2008.

On Bear Creek (Figure 3), the peak flow rate was about 862 cubic feet per second (cfs) on January 4, 2008 at 14:45. On San Francisquito Creek at Piers Lane (Figure 4), the highest peak flow rate was 1,621 cfs on January 25, 2008 at 21:30. On Los Trancos Creek at Piers Lane (Figure 5), the highest peak flow rate was 316 cfs on January 25, 2008 at 18:30.

As observed in water year 2007, recessional flows during spring 2008 occurred earlier than usual and summer baseflow in all three streams were lower than most previous years.

4.2 Precipitation

Water year 2008 rainfall recorded at the Piers Lane tipping-bucket rain gauge totaled 17.0 inches, or 92 percent of the long-term mean annual precipitation of about 18.5 inches (Rantz, 1971). Higher in the watershed, the tipping-bucket rain gauge at the Bear Creek at Sand Hill Road station recorded 21.3 inches of rain in water year 2008, or 82 percent of the long-term mean annual precipitation of about 26 inches for the station location (Rantz, 1971).

According to California Data Exchange Center (CDEC) records, water year 2008 rainfall at precipitation stations in the San Francisco Bay region was 70 to 94 percent of long-term average values. At the two index precipitation stations in the region that we have referenced in previous years, water year 2008 precipitation at Mount Hamilton was 85 percent of the long-term average values, while rainfall at the San Francisco Airport was 87 percent of the long-term average. The rainfall totals agree with our flow totals, which indicate that water year 2008 was wetter than water year 2007, but still somewhat drier than average.

4.3 Return Period of Peak Flows

Flows were moderately large on both January 4 and January 25, 2008. Even though we do not have a sufficient period of record to calculate the return period of water year 2008 peak flows at the stations that we monitor for this project, we can characterize the peak flows at the USGS gaging station on San Francisquito Creek (USGS number 11164500). The estimated peak flow for this station for water year 2008 is 1,850 cfs, which corresponds to a 2.5-year return period (40.5 percent chance of being exceeded in any year), based on the annual-peak series. This is somewhat higher than the median peak flow of 1,250 cfs, which can be taken to approximate the 2-year return period (50 percent chance of being exceeded in any year).

4.4 Unexplained Flow Surges

In the fall 2007 record, we noted a flow increase in Bear Creek that lasted for about 2 weeks (Figure 2) and was not associated with rainfall. Flow increased by about 0.4 cfs, or 180 gallons per minute. Specific conductance decreased by about 200 microsiemens (μs) during the increase in flow, consistent with addition of water to the creek that is less saline than the background level of approximately 600 μs (Figure 9). These spikes did not discernibly affect the temperature record (Figure 13).

During April 2008, we recorded several brief increases in flow for the Los Trancos Creek at Piers Lane station on April 2 and 11 (Figure 6). The water temperature did not appear to be greatly affected. These spikes were also recorded at Balance's upstream Los Trancos Creek station at Arastradero Road.

In addition to the flow surges mentioned above, we continued to note significant abrupt changes in flow (mainly *dips* in flow) at the Bear Creek station that could be due to diversions. These changes are qualitatively consistent with operation of upstream diversions by California Water Service Company;⁵ other diversions are known from the watershed, either directly from the channel or through replenishment of pumped ground water.

We have previously noted spikes of high temperature and/or high salinity at all three of the monitoring stations.

4.5 Creating a Record of Streamflow

We develop a record of streamflow in two steps. First, a record of water levels is compiled from the recorded electronic data and calibrated with field observations. Flow rates are then computed from the water levels using empirical equations developed specifically for each site from field measurements.

4.5.1 Developing a record of water levels

The monitoring equipment at the Bear Creek at Sand Hill Road station and the San Francisquito Creek at Piers Lane station includes two pressure transducers, which measure water levels in the creek at 15-minute intervals, and a Campbell Scientific CR10X datalogger to record the water-level data. The Los Trancos Creek at Piers Lane station is equipped with an ultrasonic sonar transponder connected to an American Sigma 950 flow meter and datalogger. Field measurements and observations at each station are used to calibrate the electronic record. Observations during site visits include: water level (or gage height) at the staff plate, high water marks, the presence of twig and leaf dams which may temporarily raise or lower water levels, signs of sedimentation or scour, and the specific conductance and temperature of the water (Tables 1 to 3).

⁵ Personal communication from Darin Duncan, California Water Service Co. to Marty Laporte, Stanford University, Utilities Division, May 26, 2006.

During this year, as is typically done, we applied multiple stage shifts to the electronic water-level record to account for intermittent sedimentation, leaf dams and algae growth that affect the water-level elevation at the monitoring locations. We found that observed high-water marks corresponded well (usually within 0.2 to 0.3 feet) with the recorded water-level peaks, providing additional confidence in the stage record.

4.5.2 Computing flows

Based on our periodic site visits, staff plate readings, and flow measurements (Tables 1 to 3), we create an empirical stage-to-discharge relationship (“stage-discharge rating curve”) for each gage. This rating curve is then applied to the electronic record of water levels measured by the pressure transducers (at BCSH and SFPL) and the sonar transponder (at LTPL).

At low flows, the sonar transponder values have a large amount of variation, up to about 0.3 feet per day. We consider most of this variation to be “noise” in the instrument reading that does not reflect actual changes in water levels, although a lower-amplitude (0.02-foot) diurnal pattern of water-level change is typically observed during low-flow periods. The flow record becomes particularly “noisy” at the 15-minute level of detail, which is why we present the data in daily form. Mean daily stream flow values appear to be fairly accurate because daily averaging removes most of the noise.

As with all other gaging of natural streams, some uncertainty remains (especially at high and low flows) in spite of efforts to be as precise as possible. Due to safety concerns and site limitations, we do not have manual stream flow measurements at the peak flow levels. The high end of the stage-discharge rating curves are defined by peak-flow estimates from water year 2006 (based on standard indirect peak-flow measurements made by cross-sectional and longitudinal surveys of high-water marks) (Owens and others, 2007).

5. WATER QUALITY SAMPLING APPROACH

Larry Walker Associates developed the water-quality monitoring plan for the two LTMAP stations at Piers Lane while under contract to the City of Palo Alto (LWA, 2001). Their Draft Surface Water Quality Monitoring Plan 2001/02, available from the City of Palo Alto, provides a complete description of the methods and protocols used in this study. Because the Bear Creek at Sand Hill Road stream gage is also part of the LTMAP study, the same protocols were used there as at the Piers Lane stations and results can be compared. Interested readers are referred to the water-quality monitoring plan for additional detail.

The LTMAP monitoring program is designed to measure field parameters on each sampling visit. Sediment sampling occurs from fall through spring, when flows are sufficiently elevated to transport sediment. Due to budget constraints, only flow and sediment were monitored at Bear Creek beginning in water year 2007, and at the Piers Lane stations beginning in water year 2008. Results of sampling for chemical constituents, collected four to five times annually in prior years, may be found in our previous monitoring reports.

5.1 Field Measurements and Laboratory Analyses

The current focus of the study is on characterizing water quality in the two streams during both baseflow and storm periods, particularly with regard to flow and sediment transport, as variables potentially affecting fisheries and aquatic habitat conditions.

Field Measurements

- streamflow (cubic feet per second, or cfs)
- specific conductance (microsiemens, or μs @ 25°C)
- water temperature (°C)
- dissolved oxygen (mg/L)
- pH
- qualitative remarks, for example, odors, color, clarity, (if noticeable), and anomalies

Laboratory Analyses

- total suspended solids
- bedload sediment

5.2 Exceptions and Deviations from Proposed Methods

Deviations almost inevitably occur in hydrologic studies, usually at very high or low flows, such as the responses necessary when a tree falls or other changes in the channel at the sampling location are encountered. Although no water-quality sampling was performed at the Bear Creek or Piers Lane stations in water year 2008, deviations related to the condition of the monitoring equipment at all stations are listed below: .

During the seventh year of monitoring Los Trancos Creek and San Francisquito Creek at Piers Lane, we were unable to complete the following items as they were initially outlined in the project proposal:

- Maintenance of the original pH and dissolved oxygen probes at both Piers Lane stations remains problematic, so these probes continue to perform poorly and the only available data on these parameters are from hand-held meters.
- Performance of both the original specific conductance probe and the additional probe installed in March 2007 at the Los Trancos Creek station is erratic (Figure 8). Temperature data are available from the sensor on the dissolved oxygen probe. [A “loaner” probe was installed prior to the start of Water Year 2009 and will remain in place through the close of this season.]
- The replacement specific conductance probe installed at the San Francisquito Creek station in February 2006 has transitioned from erratic to non-functional (Figure 10), although the temperature sensor still works well. [A “loaner” probe was installed in February 2009 and will remain in place through the close of the Water Year 2009 season.]

During the fifth year of monitoring at the Bear Creek at Sand Hill Road station, we were unable to complete the following items as they were initially outlined in the project proposal:

- The datalogger hardware (datalogger module) failed in late May 2008 and was replaced with a “loaner” unit about two weeks later. [The original unit was repaired by the manufacturer and reinstalled by Balance staff in February 2009.]
- Maintenance of the pH and dissolved oxygen probes remains problematic, so these probes continue to perform poorly and the only available data on these parameters are from hand-held meters.
- Since June 2008, performance of the specific conductance probe has been erratic (Figure 8); we are continuing to troubleshoot the problem. The temperature sensor still works well.

Recommendations for improving the monitoring program during water year 2009 and subsequent years are presented briefly in Chapter 7 below.

6. RESULTS AND DISCUSSION OF WATER QUALITY SAMPLING

This chapter includes a discussion of findings by individual constituent or constituent group. Results of manual measurements of specific conductance, temperature, pH, and dissolved oxygen are included in Tables 1 to 3. Results of suspended-sediment sampling during and between storms, used to estimate annual suspended-sediment yields, are presented in Table 5 (Bear Creek) and Table 6 (San Francisquito Creek and Los Trancos Creek). All laboratory reports are collected in Appendix A.

6.1 Specific Conductance

Specific conductance values during water year 2008 were within the range of previous sampling results and are generally within the expected range for the San Francisquito watershed.

Specific conductance, a widely used index for salinity or total dissolved solids (TDS), was measured in the field and recorded at field temperatures, then later converted to an equivalent value at 25°C according to the accepted relationship between specific conductance and temperature. The expected range of specific conductance in the San Francisquito Creek watershed is from about 100 to 2,000 μS (all values are normalized to 25°C). The lowest levels occur during storms, when flows are diluted with rain and fresh runoff. The highest levels are typically observed in early fall, when flows are lowest, prior to the onset of seasonal rains.

During water year 2008, specific conductance ranged from about 100 to 1,000 μS (values from Figure 9) in Bear Creek (Table 1; Figure 9) and from about 200 to 1,500 μS (values from Figure 10) in San Francisquito Creek (Table 3; Figure 10). Based solely on manual measurements, observed specific conductance ranged from about 180 to 2,000 μS in Los Trancos Creek (Table 2, Figure 8). As was observed in previous water years, specific conductance was again typically lowest in Bear Creek and highest in Los Trancos Creek. Specific conductance levels in all three streams were at the higher end of the range in spring and summer of 2007, as would be expected during a relatively-low rainfall year.

6.2 Water Temperature

Water temperatures during water year 2008 were within the range of previous measurements.

6.2.1 Water temperature affects fish

Water temperature strongly affects steelhead habitat. Although steelhead can withstand high water temperatures of 29°C for a short period of time, and 25°C for longer periods, they have progressively-increasing difficulty extracting dissolved oxygen from water at temperatures above 21°C (Lang and others, 1998) and require a larger food source to sustain their elevated metabolism (Smith, pers. comm.). Therefore, water temperatures of 21°C and below are considered to provide adequate summer habitat, and values chronically above 25°C are likely not viable for the local steelhead population.

6.2.2 Temperature monitoring probes

Each of the three stations includes one or two in-stream probes that continuously record water temperatures. Manual temperature measurements during water year 2008 site visits followed the same seasonal pattern and values recorded by the in-stream probes (Figures 11 to 13). Water temperatures were within the reported acceptable range for steelhead habitat during the water year 2008 season, despite the below-average flows which could have increased the potential for high stream temperatures.

6.2.3 Temperature differences between creeks

As observed in the six previous years (WY2002 to WY2007), water temperatures in San Francisquito Creek (Figure 11) appeared to be slightly warmer than in Los Trancos Creek during the dry season (Figure 12). Dry-season temperatures in Bear Creek (Figure 13) were similar to Los Trancos Creek and cooler than in San Francisquito Creek.

6.3 pH

In most instances, pH values during water year 2008 were within the range of previous measurements. This parameter is not considered to be a management concern.

As stated above in Section 5.3, the pH probes at all three stations were non-functional in water year 2008, so this parameter was measured occasionally using hand-held meters. pH measurements ranged from 7.5 to 8.6 in Bear Creek (Table 1, Figure 14), from 7.1 to 8.3 in Los Trancos Creek (Table 2, Figure 14), and from 7.1 to 8.6 in San Francisquito Creek (Table 3, Figure 14). pH values were similar to measurements from previous years and, once again, pH

was typically slightly higher in Los Trancos Creek than in San Francisquito Creek; pH in Bear Creek did not have a consistent pattern compared to the other two streams.

We note that fisheries biologists familiar with the northern Santa Cruz Mountains and San Francisco Peninsula streams have found that pH is very rarely a limiting factor in regards to steelhead habitat, so long as there is flow moving from pool to pool.

6.4 Dissolved Oxygen

Dissolved oxygen concentrations were occasionally low during late summer and fall, which may be limiting for biota.

As stated above in Section 5.3, the dissolved oxygen probes at the Los Trancos Creek and San Francisquito Creek stations were essentially non-functional in water year 2008 and the dissolved oxygen probe at the Bear Creek station also performed poorly, so this parameter was measured only occasionally using hand-held meters. Based on the limited set of measurements, dissolved oxygen concentrations varied between 88 and 94 percent of saturation in Bear Creek (Table 1, Figure 15), between 72 and 98 percent of saturation in Los Trancos Creek (Table 2, Figure 16), and between 67 and 98 percent of saturation in San Francisquito Creek (Table 3, Figure 17). As reported in previous years, dissolved oxygen concentrations were typically highest in Los Trancos Creek, and higher in Bear Creek than in San Francisquito Creek.

As noted in our WY2003 report (Owens and others, 2004), manual measurements of dissolved oxygen can vary considerably depending upon where in the creek the probe is placed, with values ranging from about 15 to 60 percent saturation at locations as little as one foot apart. This situation is particularly common in the fall, when the streams are full of dead leaves. Based on our monitoring data to date, we expect dissolved oxygen concentrations in all three creeks to range from 10 to 14 mg/L (90 to 100 percent saturation) during the winter and especially at high flows, when turbulence and cold ambient water temperatures promote oxygen saturation. Dissolved oxygen concentrations become more limiting for fish as streamflows decrease and temperatures rise in spring and summer. The lowest concentrations tend to occur in the fall months (c.f., Table 1), at the start of the next water year but before rains raise water levels and high flows flush accumulations of rotting leaves downstream.

6.5 Sediment

Even though water year 2008 was dry in terms of total flow, the peak flows were moderately large (approximately 2.5-year return period). Therefore, roughly average or slightly below average amounts of sediment were discharged. Sediment concentrations during water year 2008 were within the range of previous sampling results.

San Francisquito Creek is listed by the State Water Resources Control Board as impaired due to sediment loading. All creeks carry some sediment; problems can arise when creeks carry too much sediment. Biologically, too much fine sediment can reduce oxygen circulation to buried eggs, abrade fish gills, fill hiding and resting niches and impede post-storm feeding. Too much coarse sediment affects bed conditions in a number of ways that can constrain steelhead habitat, including filling pools and undercut banks, creating 'soft' beds that are prone to scour, and forming mid-channel bars that divert flows into the banks, inducing bank erosion. Excess coarse sediment can also settle out at low-gradient locations, reducing pool depths and decreasing the flood capacity of the channel.

Monitoring sediment concentrations and rates of sediment transport is important as a way of evaluating the amount of sediment being carried by the creek, to assess the mobility of spawning gravels and document changes that may signal improving or worsening conditions. Previous Balance reports have documented rates of sediment transported in various watersheds upstream from Piers Lane (c.f., Balance Hydrologics, 1996; Owens and others, 2001; Owens and Hecht, 2002), as well as the role of Searsville Lake in trapping sediment and the contributions from different geologic formations. Staff of the U.S. Geological Survey previously made measurements of suspended sediment at the long-term gage at the golf course (Brown and Jackson, 1973). In this watershed, we have observed a number of sources, both natural (e.g., bank failure, landslides) and human-caused or human-exacerbated (e.g., failure of culvert outfalls, construction erosion control measures, bank protection). Detailing these sources, however, is beyond the scope of this report.

Following convention, we distinguish two types of sediment in transport, each of which is measured during storms using specific types of samplers and sampling methods. Suspended sediment is supported by the turbulence of the water and is transported at a velocity approaching the mean velocity of flow. In the San Francisquito Creek watershed, as elsewhere in the Santa Cruz Mountains, suspended sediment consists primarily of fine sands, silts, and

clays. Bedload sediment is supported by the bed of the stream; it rolls and saltates along the bed, commonly within the lowermost 3 inches of the water column. Movement can be either continuous or intermittent, but is generally much slower than the mean velocity of the stream. At the Piers Lane stations and in the Bear Creek watershed, bedload consists primarily of coarse sands and gravels, but will also include cobbles at extreme high flows. Total sediment discharge is the sum of bedload-sediment and suspended-sediment discharges.

6.5.1 Suspended sediment

Suspended-sediment samples were collected from all three stations throughout the water year at various dates and levels of flow (Table 4) using standard methods and equipment adopted by the Federal Interagency Sedimentation Project (FISP; see Hecht, 1983). All grab samples were analyzed by Soil Control Laboratories of Watsonville, California, a state-certified laboratory. No suspended-sediment samples were collected when stream waters were visibly clear. From past experience, we have found that samples collected when the streams are clear produce no useful information because they test below the analytical reporting limit.

By multiplying the reported suspended-sediment concentrations by the streamflow at the time the sample was taken, concentrations (mg/L) were converted into an instantaneous suspended-sediment “load” (tons/day), as shown in Tables 5 and 6. We then plotted sediment load as a function of streamflow to create suspended-sediment rating curves describing the general trend of the data points for each creek (Figures 18 and 19). We also applied the suspended-sediment rating curves to the records of streamflow (at 15-minute intervals) to calculate a total annual suspended-sediment load for each creek (Forms 4 to 6). Interpretation of suspended-sediment rates and total loads is discussed in Section 6.5.3 below.

6.5.2 Bedload sediment

The *Draft Surface Water Quality Monitoring Plan 2001/02* (LWA, 2001) does not include consideration or protocols for measurements of bedload-sediment transport. At all three LTMAP gaging stations discussed in this report, the threshold for significant bedload transport occurs at flow depths and velocities that border on being too deep to sample safely by wading. No bedload samples were collected during water year 2008, yet bedload monitoring is one effective way of characterizing bed conditions for anadromy (Hecht and Enkeboll, 1981; Roques and Angelo, 2004; Hecht and Owens, 2006). If studying how bed conditions constrain

anadromous fish populations in the Santa Cruz Mountains becomes an objective of this program, then a greater emphasis can be placed on collecting bedload sediment samples.

Although we have only a limited number of bedload-sediment measurements on Bear Creek and on Los Trancos Creek at Piers Lane, as compared to the number of suspended-sediment samples, we have constructed bedload rating curves for those stations (Figures 18 and 19). Bedload samples are converted to a discharge rate (in units of tons per day) and then plotted as a function of flow. As expected, sediment discharge increases as flow increases. We also applied the bedload rating curve to the record of streamflow (at 15-minute intervals) to calculate annual bedload totals for Bear Creek (Form 4 and Table 4) and Los Trancos Creek (Form 5 and Table 4). Interpretation of bedload-sediment rates and total loads for these two stations is discussed in Section 6.5.3 below.

6.5.3 Sediment discussion

Suspended-sediment rating curves for San Francisquito, Los Trancos, and Bear Creeks were similar to those produced for the previous year (water year 2007).

Comparison of the suspended-sediment rating curves for the Los Trancos Creek and San Francisquito Creek at Piers Lane stations (Figure 18) with the rating curve for the Bear Creek station (Figure 19) shows that Los Trancos Creek generally carries higher suspended-sediment loads at a given flow than San Francisquito Creek or Bear Creek. Higher rates of transport in *tributary* streams at a given flow is a typical condition and nearly universal throughout the Bay Area (c.f., Hecht, 1983), since tributary watersheds tend to be steeper and more subject to erosion due to higher flow velocities. In addition, suspended-sediment concentrations in San Francisquito Creek are diluted by outflows from Searsville Lake, which traps a large proportion of the sediment load from tributary streams higher in the watershed. We compared the sediment rating curve for Bear Creek to rating curves of other creeks that we monitor in the watershed, and found that sediment-discharge rates (as a function of flow) for Bear Creek are lower than rates for Corte Madera or Los Trancos Creeks.

It is important to note that storm flow in San Francisquito Creek is typically at twice the rate of flow in Bear Creek⁶, and usually five or more times greater than flow in Los Trancos Creek

⁶ The relationship between flow at the Bear Creek at Sand Hill Road station and flow at San Francisquito Creek at Piers Lane varies seasonally with the amount of outflow from Searsville Lake. Typically,

(Figure 2), so San Francisquito Creek still transports more total sediment load. This is evident in the annual sediment summaries (Forms 4 to 6), which show that the calculated total suspended-sediment load in San Francisquito Creek was about 7,300 tons in water year 2008, compared to about 1,100 tons in Bear Creek and 1,400 tons in Los Trancos Creek. The suspended-sediment total for San Francisquito Creek seems to us to be a little high (alternately, the Bear Creek total could be too low): we calculated the suspended-sediment total flowing out of Searsville Lake to be approximately 950 tons, and the San Francisquito total should be a little larger than the summation of the Searsville and Bear Creek totals.

Sediment discharge rates at each of the stations show a strong dependence on flow at the time of the measurement; when flow is higher, the creeks carry more sediment. Therefore, sediment totals for each stream also vary from year to year depending on the amount of rainfall and the size of the largest flood peak (Table 4). This concept of “episodicity” is useful for interpreting the sediment measurements within the context of the inter-annual variability in climate conditions. Rather than trying to calculate an average sediment discharge per year, we acknowledge that there will be large year-to-year variability in sediment discharge.

differences in flow between the two sites are smaller at the start of the wet season, when the water level in the lake is below the spillway. Later in the wet season, differences are greater once the lake begins to spill freely.

7. FUTURE MONITORING AND RECOMMENDATIONS

The following recommendations are offered for consideration by the LTMAP working group based on our experience and observations since inception of monitoring:

1. We plan to monitor flow and sediment transport over a wide range of events during water year 2009, but will not sample chemical constituents at any of the three sites. At the Bear Creek at Sand Hill Road station, the gaging program will be maintained at a minimal (baseline) level that will still provide valuable data on streamflows, and sediment grab samples will be collected in conjunction with sampling at other local project sites.
2. Balance has been and is working with Stanford University and Regional Water Quality Control Board staff to develop useful metrics to evaluate sediment conditions in the creeks of the San Francisquito watershed. This effort could potentially enhance the current LTMAP monitoring program through application of new tools and a wider range of monitoring methods focused on sediment conditions as they relate to stream biota and habitat.
3. The mal-functioning datalogger module at the Bear Creek at Sand Hill Road station should be repaired or replaced, and substituted for the “loaner” unit installed in June 2008. [The module was subsequently repaired and re-installed in February 2009.]
4. The specific conductance probes at both the Los Trancos Creek and San Francisquito Creek at Piers Lane stations are broken and need to be repaired or replaced. [Specific conductance at both stations is being measured using “loaner” probes that will remain in place through the close of Water Year 2009.]

8. LIMITATIONS

Analyses and information included in this report are intended for use at the watershed scale and for the planning and long-term monitoring purposes described above. Analyses of channels and other water bodies, rocks, earth properties, topography and/or environmental processes are generalized to be useful at the scale of a watershed, both spatially and temporally. Information and interpretations presented in this report should not be applied to specific projects or sites without the expressed written permission of the authors, nor should they be used beyond the particular area to which we have applied them. Balance Hydrologics, Inc. should be consulted prior to applying the contents of this report to evaluating water supply or any out-of-stream uses not specifically cited in this report.

Readers who have additional pertinent information, who observed changed conditions, or who may note material errors should contact us with their findings at the earliest possible date, so that timely changes may be made.

9. ACKNOWLEDGEMENTS

We believe that this is an important study and would like to thank those individuals and groups whose contributions to the planning and implementation of the LTMAP project and this multi-component study have been invaluable, including: Marty Laporte, Philippe Cohen, Tom Zigterman, Susan Witebsky, and Annette Walton (Stanford University), Geoff Brosseau (BASMAA), and Phil Bobel (City of Palo Alto Regional Water Quality Control Plant).

We are also grateful to Armand Ruby (formerly of Larry Walker Associates), Brad Eggleston and Margaret Zittle (City of Palo Alto Regional Water Quality Control Plant), and the many other individuals who have contributed ideas or have assisted us in other ways to make this study feasible, safe and useful.

Key funding for monitoring equipment installation and/or monitoring, without which this study could not have proceeded, has been provided by: the City of Palo Alto Regional Water Quality Control Plant; Stanford University, Utility Division; Stanford Real Estate Office; SLAC National Accelerator Laboratory (SLAC); and the Jasper Ridge Biological Preserve.

10. REFERENCES

- Balance Hydrologics, Inc., 1996, Sedimentation and channel dynamics of the Searsville Lake watershed and Jasper Ridge Biological Preserve, San Mateo County, California: Consulting report prepared for Jasper Ridge Biologic Preserve, 73 p. + appendices
- Brown, W. M., III, and Jackson, L.E., Jr., 1973, Erosional and depositional provinces and sediment transport in the south and central part of the San Francisco Bay region, California: U.S. Geological Survey Open-File Report MF-515. 21 p.
- Hecht, B., 1983, Substrate enhancement/sediment management study: Lagunitas Creek, Marin County. Sediment transport and bed conditions, 1979-1982: HEA report prepared for the Marin Municipal Water District, 173 p.
- Hecht, B., and Enkeboll, R., 1981, Channel and substrate conditions, sediment transport, and alternative approaches for sediment management in Zayante Creek below the proposed Zayante Dam: H. Esmaili & Associates report submitted to D.W. Kelley, Aquatic Biologist, 93 p.
- Hecht, B. and Owens, J., 2006, Sediment discharge in unregulated streams tributary to San Francisco and Suisun Bays And adjoining areas: 2006, Bay Delta conference, abs.
- Lang, J., Oppenheim, B., and Knight, R., 1998, Southern steelhead (*Oncorhynchus mykiss*) habitat suitability survey of the Santa Margarita River, San Mateo, and San Onofre Creeks on Marine Corps Base Camp Pendleton, California: Report prepared by the U.S. Fish and Wildlife Service Coastal California Fish and Wildlife Office, Arcata, California for the Assistant Chief of Staff, Environmental Security, Environmental and Natural Resource Office, Marine Corps Base Camp Pendleton
- Larry Walker Associates, 2001, Draft surface water quality monitoring plan 2001/02, San Francisquito Creek watershed, Consulting report prepared for the City of Palo Alto, 27 p. + appendices.
- Owens, J., and Hecht, B., 2002, Annual hydrologic record and preliminary sediment budget for Los Trancos Creek above Stanford's Felt Lake diversion, Santa Clara and San Mateo Counties, California, Data report for water year 2002: Consulting report prepared by Balance Hydrologics for the Utilities Division, Stanford University, 13 p.
- Owens, J., Mallory, B., Shaw, D., White, C., and Hecht, B., 2001, Water quality and streamflow monitoring of the Bear Creek watershed, Woodside, San Mateo County, California: first year data report, water year 2000: Consulting report prepared by Balance Hydrologics for San Francisquito Watershed Council, 49 p. + appendices
- Owens, J., Mallory, B., White, C., and Hecht, B., 2004, Water quality and streamflow monitoring of the Bear Creek watershed, Woodside, San Mateo County, California: second year data report, water year

2001: Consulting report prepared by Balance Hydrologics for San Francisquito Watershed Council, 35 p. + appendices

Owens, J., White, C., Gartner, J. and B. Hecht, 2006, Water quality and streamflow monitoring of San Francisquito and Los Trancos Creeks at Piers Lane, and Bear Creek at Sand Hill Road, water year 2005, long-term monitoring and assessment program, San Mateo and Santa Clara Counties: consulting report prepared by Balance Hydrologics for Stanford University Utilities Division, 87 p. + appendices

Owens, J., White, C., Gartner, J., Rubin, Z., and B. Hecht, 2007. Water quality and streamflow monitoring of San Francisquito and Los Trancos Creeks at Piers Lane, and Bear Creek at Sand Hill Road, water year 2006, long-term monitoring and assessment program, San Mateo and Santa Clara Counties: consulting report prepared by Balance Hydrologics for Stanford University Utilities Division, 89 p. + appendices

Owens, J., White, C., Gartner, J., Rubin, Z., and B. Hecht, 2008. Water quality and streamflow monitoring of San Francisquito and Los Trancos Creeks at Piers Lane, and Bear Creek at Sand Hill Road, water year 2007, long-term monitoring and assessment program, San Mateo and Santa Clara Counties: consulting report prepared by Balance Hydrologics for Stanford University Utilities Division, 84 p. + appendices

Owens, J., White, C., Mallory, B. and Hecht, B., 2003, Water quality and streamflow monitoring of San Francisquito and Los Trancos Creeks at Piers Lane, water year 2002, long-term monitoring and assessment program, San Mateo and Santa Clara Counties: Consulting report prepared by Balance Hydrologics for Stanford University Utilities Division, 49 p. + appendices

Owens, J., White, C., Mallory, B. and Hecht, B., 2004 Water quality and streamflow monitoring of San Francisquito and Los Trancos Creeks at Piers Lane, water year 2003 long-term monitoring and assessment program, San Mateo and Santa Clara Counties: Consulting report prepared by Balance Hydrologics for Stanford University Utilities Division, 57 p. + appendices

Owens, J., White, C., Mallory, B. Hecht, B., and Gartner, J., 2005 Water quality and streamflow monitoring of San Francisquito and Los Trancos Creeks at Piers Lane, and Bear Creek at Sand Hill Road, water year 2004, long-term monitoring and assessment program, San Mateo and Santa Clara Counties: Consulting report prepared by Balance Hydrologics for Stanford University Utilities Division, 90 p. + appendices

Rantz, S.E., 1971. Precipitation depth-duration-frequency relations in the San Francisco Bay Region, California with isohyetal map showing mean annual precipitation: U.S. Geological Survey Basic Data Contribution 25.

Roques, D., and Angelo, M., 2004, Regional sediment assessment – project report for phase I, module 4: Regional Water Quality Control Board, Central Coast Region, 24 p.

FORMS

Water Year: 2008
Stream: Bear Creek
Station: at Sand Hill Road **BCSH**
County: San Mateo County, CA

Form 1. Annual Hydrologic Record

Station Location / Watershed Descriptors

Latitude: 37 24' 40", Longitude: 122 14' 28" Jasper Ridge Biological Preserve, Stanford, CA.
 Gage is installed on left bank, about 200 feet downstream from Sand Hill Rd. Staff-plate pool is eroded into hard sandstone; underflow is thought to be minimal. Land use includes forested open space, and suburban uses in valleys. Drainage area above gage is 11.7 sq. miles.

Mean annual flow (MAF)


MAF for the period of record (2000 - 2008) is 7.42 cubic feet per second (cfs)
 Mean Daily Flow for WY2008 = 3.36 cfs.; 2007 = 1.75 cfs.; 2006 = 18.33 cfs.; 2005 = 11.21 cfs.

Peak Flows

Date	Time (24-hr)	Gage Ht. (feet)	Discharge (cfs)	Date	Time (24-hr)	Gage Ht. (feet)	Discharge (cfs)
12/7/07	3:00	2.07	7	1/25/08	20:00	5.70	431
12/18/07	13:00	2.68	45	2/3/08	0:45	4.32	201
12/20/07	4:00	2.91	64	2/23/08	19:15	2.51	33
1/4/08	14:45	7.29	822				

The peak for the period of record (Oct. 1999 to Sept. 2008) was 3,800 cfs on Dec. 31, 2005

Map



Period of Record

Station operated May to Nov. 1997, and October 1999 to present.
 Flow, sediment transport, water quality, and specific conductance measured periodically. Gaging sponsored by Jasper Ridge Biological Preserve and Stanford Linear Accelerator Center.

WY 2008 Daily Mean Flow (cubic feet per second)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT
1	0.11	0.44	0.11	0.64	35.86	3.23	1.18	0.63	0.4	0.26	0.18	0.16
2	0.06	0.51	0.13	0.64	32.17	4.58	1.16	0.61	0.4	0.26	0.16	0.08
3	0.03	0.66	0.12	1.40	98.95	3.06	1.13	0.61	0.4	0.22	0.17	0.06
4	0.02	0.66	0.39	238.35	22.52	3.79	1.12	0.64	0.4	0.22	0.24	0.02
5	0.02	0.66	0.32	58.75	10.39	2.89	1.14	0.65	0.4	0.19	0.25	0.05
6	0.03	0.65	0.54	22.68	5.43	1.96	1.11	0.60	0.4	0.33	0.19	0.01
7	0.03	0.72	2.38	6.10	3.39	2.11	1.08	0.55	0.3	0.18	0.17	0.07
8	0.02	0.72	0.29	7.51	2.73	2.16	1.10	0.64	0.4	0.18	0.10	0.11
9	0.14	0.51	0.18	4.38	2.03	2.29	1.08	0.59	0.4	0.18	0.09	0.10
10	1.11	0.47	0.17	2.89	2.06	2.05	1.09	0.53	0.3	0.21	0.23	0.09
11	0.14	0.80	0.16	1.78	2.04	1.88	1.01	0.52	0.3	0.33	0.17	0.15
12	1.15	0.56	0.14	1.05	1.80	1.80	0.92	0.52	0.3	0.28	0.08	0.16
13	0.56	0.53	0.16	0.95	2.44	1.81	0.86	0.51	0.3	0.36	0.11	0.12
14	0.20	0.55	0.16	1.31	2.67	1.73	0.88	0.46	0.33	0.19	0.14	0.24
15	0.19	0.57	0.14	1.81	2.50	1.89	0.84	0.46	0.34	0.25	0.05	0.08
16	0.22	0.46	0.12	1.71	2.36	1.55	0.83	0.51	0.34	0.27	0.03	0.09
17	0.23	0.37	1.06	1.55	2.29	1.49	0.83	0.59	0.32	0.25	0.15	0.07
18	0.18	0.38	8.23	1.42	2.23	1.55	0.79	0.65	0.28	0.21	0.08	0.14
19	0.15	0.39	1.33	1.27	3.78	1.60	0.84	0.64	0.30	0.23	0.07	0.12
20	0.15	0.43	9.68	1.12	7.00	1.50	0.77	0.47	0.25	0.29	0.15	0.10
21	0.16	0.40	1.10	2.04	5.34	1.44	0.78	0.40	0.24	0.24	0.14	0.18
22	0.17	0.29	0.74	3.11	8.60	1.41	0.81	0.41	0.28	0.19	0.08	0.14
23	0.14	0.23	0.64	3.17	10.70	1.35	0.96	0.44	0.35	0.25	0.10	0.19
24	0.07	0.20	0.59	3.88	54.04	1.51	0.83	0.50	0.29	0.18	0.22	0.09
25	0.05	0.23	0.56	161.61	28.83	1.51	0.73	0.56	0.24	0.23	0.16	0.08
26	0.09	0.23	0.56	92.70	14.40	1.28	0.70	0.54	0.28	0.13	0.13	0.09
27	0.22	0.16	0.59	40.52	9.86	1.30	0.72	0.5	0.30	0.21	0.13	0.04
28	0.15	0.13	0.73	44.20	5.46	1.27	0.72	0.4	0.28	0.19	0.11	0.16
29	0.19	0.12	0.75	13.78	3.00	1.28	0.84	0.5	0.27	0.27	0.08	0.13
30	0.19	0.12	0.68	10.87		1.24	0.66	0.4	0.28	0.16	0.04	0.11
31	0.41		0.64	26.25		1.16		0.4		0.27	0.09	
MEAN	0.21	0.44	1.08	24.50	13.27	1.93	0.92	0.53	0.32	0.23	0.13	0.11
MAX. DAY	1.15	0.80	9.68	238.35	98.95	4.58	1.18	0.65	0.43	0.36	0.25	0.24
MIN. DAY	0.02	0.12	0.11	0.64	1.80	1.16	0.66	0.40	0.24	0.13	0.03	0.01
cfs days	6.6	13.1	33.4	759.4	384.9	59.7	27.5	16.5	9.7	7.2	4.1	3.2
ac-ft	13.1	26.1	66.2	1506.4	763.4	118.4	54.5	32.7	19.2	14.3	8.2	6.4

Monitor's Comments

- We collected a continuous stage record from October 1, 2007 to May 26, 2008 and June 14 to September 30, 2008. The flow record for the period from 5/27/08 - 6/13/08 has been estimated by correlation from the SFPL record of flow. This period is shown in *italics* and with one less significant digit
- Diversions upstream of the gaging location affect flow in the creek. Occasional flow alterations (both additions and subtractions) were recorded.
- Multiple stage shifts were applied to the rating equation. Stage shifts adjust for local scour and fill in addition to water-level changes due to algal growth or dams caused by accumulation of fallen leaves and branches
- Daily values with more than 2 to 3 significant figures result from electronic calculations, no additional precision is implied.

Water Year		
2008 Totals:		
Mean daily flow	3.62	(cfs)
Max. daily flow	238	(cfs)
Min. daily flow	0.01	(cfs)
Annual total	1,325	(cfs-days)
Annual total	2,629	(ac-ft)

Water Year: 2008
Stream: Los Trancos Creek
Station: Piers Lane **LTPL**
County: San Mateo County, CA

Form 2. Annual Hydrologic Record

Station Location / Watershed Descriptors

Latitude: 37° 24' 48" N, Longitude: 122° 11' 29" W, in San Mateo County, CA. The gaging station is located under Piers Lane bridge at Los Trancos Creek. Land use includes open space, sports fields, small commercial areas, and low-density residential. There is a water diversion about 1.8 miles upstream. Los Trancos Creek watershed area above gaging station = 7.8 square miles.

Mean annual flow (MAF)


MAF for the period of record (2003-2008) is 3.09 cubic feet per second (cfs)
 Mean Daily Flow for WY2008 = 1.80 cfs.; 2007 = 0.75 cfs.; 2006 = 7.09 cfs.; 2005 = 3.56 cfs.

Peak Flows

Date	Time (24-hr)	Gage Ht. (feet)	Discharge (cfs)	Date	Time (24-hr)	Gage Ht. (feet)	Discharge (cfs)
1/4/08	12:45	5.06	255	1/27/08	23:45	2.52	66
1/5/08	16:00	3.27	110	2/3/08	0:00	2.24	43
1/25/08	18:30	5.64	316	2/23/08	19:00	2.32	50
1/27/08	2:15	2.42	57	2/24/08	13:30	2.44	59

The peaks (for the period of record Oct. 2002 to Sept. 2008) was 640 cfs on Dec. 16, '02 and Dec. 31, '06.

Map



Period of Record

Equipment installed October 2001. Periodic site visits to measure flow, make observations, and collect water quality samples have been made since February 2002. Gaging sponsored by Stanford University Utilities Division.

WY 2008 Daily Mean Flow (cubic feet per second)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT
1	0.02	0.06	0.07	0.12	8.20	3.75	1.16	0.83	0.40	0.12	0.04	0.04
2	0.02	0.06	0.08	0.12	8.95	3.57	1.26	1.23	0.35	0.13	0.03	0.04
3	0.02	0.06	0.08	0.67	17.74	3.29	1.03	1.06	0.29	0.13	0.03	0.03
4	0.02	0.06	0.32	94.13	5.68	2.90	1.05	0.61	0.27	0.12	0.03	0.03
5	0.02	0.06	0.08	30.75	4.56	2.07	1.01	0.74	0.27	0.12	0.04	0.02
6	0.02	0.06	0.16	10.50	4.36	2.08	1.08	0.66	0.24	0.13	0.03	0.02
7	0.02	0.07	0.36	4.96	4.01	2.02	1.16	0.68	0.23	0.11	0.04	0.02
8	0.02	0.07	0.08	3.78	3.82	1.96	1.65	0.66	0.21	0.11	0.04	0.03
9	0.02	0.06	0.08	2.35	3.58	1.73	1.51	0.65	0.19	0.10	0.04	0.03
10	0.35	0.07	0.07	0.86	3.44	1.63	1.63	0.50	0.17	0.10	0.04	0.03
11	0.03	0.28	0.08	0.60	3.25	1.58	1.44	0.55	0.18	0.09	0.04	0.03
12	0.81	0.06	0.08	0.54	2.07	1.62	1.25	0.61	0.15	0.10	0.04	0.03
13	0.09	0.07	0.07	0.43	1.02	1.82	1.11	0.51	0.12	0.09	0.05	0.04
14	0.06	0.06	0.07	0.44	0.79	1.63	1.07	0.41	0.11	0.08	0.05	0.03
15	0.06	0.07	0.07	0.45	0.62	2.00	1.14	0.36	0.13	0.08	0.06	0.03
16	0.06	0.07	0.08	0.38	0.50	2.38	1.26	0.65	0.12	0.07	0.06	0.03
17	0.06	0.06	0.16	0.39	0.48	1.96	0.98	0.30	0.13	0.07	0.06	0.03
18	0.05	0.07	1.96	0.46	0.51	1.54	1.08	0.28	0.12	0.06	0.07	0.03
19	0.06	0.07	0.15	0.45	2.74	1.48	0.98	0.27	0.12	0.06	0.08	0.04
20	0.06	0.07	1.41	0.53	2.91	1.52	0.98	0.32	0.12	0.06	0.09	0.04
21	0.06	0.07	0.12	1.27	1.51	1.35	1.09	0.31	0.11	0.06	0.07	0.03
22	0.06	0.06	0.12	4.51	1.84	1.35	1.14	0.34	0.09	0.05	0.06	0.03
23	0.05	0.07	0.12	1.94	7.66	1.28	1.35	0.33	0.11	0.04	0.06	0.02
24	0.05	0.08	0.13	1.24	22.43	1.29	1.09	0.36	0.13	0.04	0.05	0.02
25	0.05	0.08	0.12	124.52	8.41	1.32	1.04	0.34	0.14	0.04	0.05	0.03
26	0.05	0.06	0.14	42.65	4.69	1.36	0.86	0.35	0.13	0.04	0.05	0.03
27	0.05	0.07	0.14	21.04	3.75	1.22	0.76	0.37	0.13	0.04	0.04	0.03
28	0.05	0.07	0.16	21.80	3.66	1.48	0.69	0.37	0.12	0.04	0.04	0.02
29	0.06	0.08	0.16	6.73	3.85	1.38	0.76	0.41	0.13	0.04	0.04	0.03
30	0.06	0.07	0.10	6.14		1.19	0.79	0.37	0.13	0.04	0.04	0.03
31	0.07		0.12	9.54		1.16		0.40		0.04	0.04	
MEAN	0.08	0.07	0.22	12.72	4.72	1.84	1.11	0.51	0.17	0.08	0.05	0.03
MAX. DAY	0.81	0.28	1.96	124.52	22.43	3.75	1.65	1.23	0.40	0.13	0.09	0.04
MIN. DAY	0.02	0.06	0.07	0.12	0.48	1.16	0.69	0.27	0.09	0.04	0.03	0.02
cfs days	2.5	2.2	6.9	394.3	137.0	56.9	33.4	15.8	5.1	2.4	1.5	0.9
ac-ft	4.9	4.4	13.8	782.1	271.8	112.9	66.3	31.4	10.2	4.7	2.9	1.8

Monitor's Comments

1. We collected a continuous record for the entire water year.
2. Multiple stage shifts were applied to the rating equation; stage shifts adjust for local scour or fill and leaf debris build-up.
3. The upper portion of the rating curve is based on several high-flow estimates. (Calculated using the "slope-area" method.)
4. Daily values with more than 2 to 3 significant figures result from electronic calculations; no additional precision is implied.
5. There is a surface-water diversion and fish ladder, about 1.8 miles upstream of this station, which may divert water out of Los Trancos Creek during the period from December 1 to May 1.

Water Year 2008 Totals:

Mean daily flow	1.80	(cfs)
Max. daily flow	125	(cfs)
Min. daily flow	0.02	(cfs)
Annual total	659	(cfs-days)
Annual total	1,307	(ac-ft)

Water Year: 2008
Stream: San Francisquito Creek
Station: Piers Lane **SFPL**
County: San Mateo County, CA

Form 3. Annual Hydrologic Record

Station Location / Watershed Descriptors

Latitude: 37° 24' 48" N, Longitude: 122° 11' 29" W in San Mateo County, CA. The gaging station is located directly under Piers Lane bridge at San Francisquito Creek, immediately upstream of its confluence with Los Trancos Creek. Land use includes open space, low-density residential, and some commercial uses. The watershed area above gaging station = 29.9 square miles.

Mean Annual Flow


Mean annual flow for the period of record is (2002-2008) is 17.9 cfs.
 Mean daily flow for water year 2008 was 10.43 cfs; 2007 was 4.88 cfs; water year 2006 was 40.09 cfs

Selected Peak Flows

Date	Time (24-hr)	Gage Ht. (feet)	Discharge (cfs)	Date	Time (24-hr)	Gage Ht. (feet)	Discharge (cfs)
10/12/07	17:00	4.07	10	1/25/08	21:30	8.86	1,621
12/20/07	7:00	4.91	65	2/1/08	2:30	5.97	250
1/4/08	17:00	8.79	1,613	2/3/08	4:30	6.64	483
1/5/08	7:30	6.47	438	2/24/08	16:30	6.00	269

The peak for the period of record (October 2002 to Sept. 2008) was 4,300 cfs on Dec. 31, 2005

Map



Period of Record

Equipment installed October 2001. Periodic site visits to measure flow, make observations, and collect water quality samples have been made since February 2002. Gaging sponsored by Stanford University Utilities Division.

WY 2008 Daily Mean Flow (cubic feet per second)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT
1	0.03	0.30	0.14	0.65	123.65	13.10	4.19	1.46	0.43	0.20	0.06	0.05
2	0.03	0.22	0.15	0.65	61.50	14.38	4.12	1.40	0.42	0.20	0.08	0.02
3	0.02	0.29	0.16	1.24	273.38	10.29	4.18	1.48	0.42	0.18	0.06	0.02
4	0.02	0.35	0.53	550.60	71.02	10.93	3.81	1.62	0.38	0.18	0.04	0.03
5	0.01	0.37	0.32	198.09	37.52	10.04	3.86	1.34	0.37	0.15	0.02	0.03
6	0.02	0.37	0.43	97.29	25.27	8.92	3.70	1.35	0.37	0.15	0.12	0.02
7	0.02	0.39	3.22	24.50	18.42	8.85	3.55	1.26	0.34	0.18	0.12	0.02
8	0.01	0.42	0.45	20.10	15.00	8.50	3.46	1.20	0.42	0.21	0.11	0.02
9	0.01	0.40	0.24	19.28	11.62	8.68	3.45	1.19	0.37	0.16	0.05	0.02
10	1.79	0.29	0.18	11.92	9.84	8.13	3.44	1.02	0.33	0.13	0.04	0.04
11	0.56	0.70	0.16	7.67	8.89	7.63	3.47	1.03	0.32	0.11	0.02	0.06
12	1.56	0.32	0.15	5.04	7.63	7.25	3.54	1.07	0.28	0.14	0.03	0.08
13	1.11	0.26	0.14	3.90	7.55	7.74	3.38	0.91	0.27	0.22	0.04	0.09
14	0.24	0.25	0.13	3.38	7.18	7.45	3.02	0.75	0.30	0.27	0.06	0.10
15	0.16	0.26	0.15	3.85	6.23	7.57	2.76	0.73	0.30	0.21	0.05	0.11
16	0.14	0.28	0.16	3.33	5.73	6.50	2.64	0.72	0.30	0.16	0.03	0.11
17	0.16	0.23	0.87	2.86	5.35	5.89	2.46	0.72	0.29	0.15	0.02	0.12
18	0.17	0.21	14.16	2.50	5.26	5.99	2.28	0.78	0.27	0.18	0.02	0.08
19	0.15	0.17	2.96	2.33	7.48	6.18	2.59	0.78	0.25	0.17	0.02	0.08
20	0.12	0.19	15.55	2.21	23.03	5.79	2.02	0.71	0.25	0.13	0.02	0.11
21	0.10	0.22	1.72	3.16	14.35	5.38	2.04	0.54	0.23	0.16	0.02	0.09
22	0.08	0.12	0.96	10.79	20.98	5.33	2.23	0.48	0.17	0.18	0.01	0.06
23	0.12	0.10	0.76	8.65	27.92	5.21	2.99	0.45	0.14	0.16	0.04	0.06
24	0.16	0.11	0.71	8.71	121.40	5.20	2.62	0.44	0.23	0.10	0.07	0.04
25	0.07	0.12	0.64	530.02	83.76	5.38	2.32	0.49	0.22	0.09	0.03	0.10
26	0.04	0.14	0.63	368.76	40.42	4.82	2.21	0.51	0.17	0.08	0.06	0.12
27	0.02	0.18	0.60	126.49	30.03	4.61	2.02	0.48	0.18	0.05	0.07	0.10
28	0.10	0.17	0.77	122.86	21.57	4.47	1.88	0.44	0.21	0.07	0.03	0.07
29	0.09	0.16	0.90	48.08	16.02	5.05	1.99	0.45	0.21	0.04	0.03	0.07
30	0.07	0.14	0.85	43.27	4.64	1.91	0.45	0.21	0.03	0.03	0.02	0.07
31	0.21		0.70	58.19		4.18		0.43		0.12	0.01	
MEAN	0.24	0.26	1.60	73.88	38.21	7.23	2.94	0.86	0.29	0.15	0.05	0.07
MAX. DAY	1.79	0.70	15.55	550.60	273.38	14.38	4.19	1.62	0.43	0.27	0.12	0.12
MIN. DAY	0.01	0.10	0.13	0.65	5.26	4.18	1.88	0.43	0.14	0.03	0.01	0.02
cfs days	7	8	49	2290	1108	224	88	27	9	5	1	2
ac-ft	15	15	98	4543	2198	444	175	53	17	9	3	4

Monitor's Comments

- We collected a continuous record for the entire water year.
- Multiple stage shifts were applied to the rating equation; stage shifts adjust for local scour or fill.
- Daily values with more than 2 to 3 significant figures result from electronic calculations; no additional precision is implied.
- Flow is regulated by multiple diversions and an upstream reservoir (Searsville Lake), plus possible return flows from applied imported water.

Water Year 2008 Totals:		
Mean daily flow	10.43	(cfs)
Max. daily flow	551	(cfs)
Min. daily flow	0.01	(cfs)
Annual tota	3,818	(cfs-days)
Annual tota	7,574	(ac-ft)

Form 4. Annual sediment-discharge record, Bear Creek at Sand Hill Road, water year 2008

Water Year: **2008**
 Stream: Bear Creek
 Station: at Sand Hill Road **BCSH**
 County: San Mateo County, CA

**Total annual sediment discharge
 (suspended- plus bedload-sediment discharge)**
WY 2008: 1,231 tons

WY 2008 Daily Suspended-Sediment Discharge(tons)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT	
1	0.0	0.0	0.0	0.0	8.4	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
2	0.0	0.0	0.0	0.0	18.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
3	0.0	0.0	0.0	0.0	66.4	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
4	0.0	0.0	0.0	633.9	2.7	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
5	0.0	0.0	0.0	26.1	0.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
6	0.0	0.0	0.0	3.3	0.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
7	0.0	0.0	0.1	0.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
8	0.0	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
9	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
11	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
12	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
13	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
14	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
15	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
18	0.0	0.0	0.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
19	0.0	0.0	0.0	0.0	0.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
20	0.0	0.0	1.6	0.0	0.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
21	0.0	0.0	0.0	0.0	0.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
22	0.0	0.0	0.0	0.1	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
23	0.0	0.0	0.0	0.1	0.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
24	0.0	0.0	0.0	0.1	20.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
25	0.0	0.0	0.0	281.5	4.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
26	0.0	0.0	0.0	73.9	1.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
27	0.0	0.0	0.0	11.0	0.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
28	0.0	0.0	0.0	11.8	0.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
29	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
30	0.0	0.0	0.0	0.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
31	0.0	0.0	0.0	10.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Qss Annual
TOTAL	0	0	3	1054	126	1	0	0	0	0	0	0	1,184
Max.day	0	0	2	634	66	0	0	0	0	0	0	0	634

WY 2008 Daily Bedload-Sediment Discharge(tons)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT	
1	0.0	0.0	0.0	0.0	0.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
2	0.0	0.0	0.0	0.0	0.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
3	0.0	0.0	0.0	0.0	2.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
4	0.0	0.0	0.0	25.4	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
5	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
6	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
11	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
12	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
13	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
14	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
15	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
18	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
19	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
20	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
21	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
22	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
23	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
24	0.0	0.0	0.0	0.0	0.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
25	0.0	0.0	0.0	11.3	0.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
26	0.0	0.0	0.0	3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
27	0.0	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
28	0.0	0.0	0.0	0.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
29	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
31	0.0	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Qbed Annual
TOTAL	0	0	0	42	5	0	0	0	0	0	0	0	47
Max.day	0	0	0	25	3	0	0	0	0	0	0	0	25

Daily values are based on calculations of sediment discharge at 15-minute intervals.
 Multiple sediment-discharge rating curves were used for different periods of the year and ranges of flow.
 Daily values with more than 2 significant figures result from electronic calculations. No additional precision is implied.

Form 5. Annual sediment-discharge record, Los Trancos Creek at Piers Lane, water year 2008

Water Year: **2008**
 Stream: Los Trancos
 Station: at Piers Lane **LTPL**
 County: San Mateo County, CA

Total annual sediment discharge
 (suspended- plus bedload-sediment discharge)
WY 2008: 1,580 tons

Daily Suspended-Sediment Discharge (tons)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT	
1	0.0	0.0	0.0	0.0	1.9	0.4	0.0	0.0	0.0	0.0	0.0	0.0	
2	0.0	0.0	0.0	0.0	3.9	0.3	0.0	0.1	0.0	0.0	0.0	0.0	
3	0.0	0.0	0.0	0.0	10.1	0.3	0.0	0.0	0.0	0.0	0.0	0.0	
4	0.0	0.0	0.0	431.9	0.8	0.2	0.0	0.0	0.0	0.0	0.0	0.0	
5	0.0	0.0	0.0	43.3	0.5	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
6	0.0	0.0	0.0	3.1	0.5	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
7	0.0	0.0	0.0	0.7	0.4	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
8	0.0	0.0	0.0	0.4	0.4	0.1	0.1	0.0	0.0	0.0	0.0	0.0	
9	0.0	0.0	0.0	0.2	0.3	0.1	0.1	0.0	0.0	0.0	0.0	0.0	
10	0.0	0.0	0.0	0.0	0.3	0.1	0.1	0.0	0.0	0.0	0.0	0.0	
11	0.0	0.0	0.0	0.0	0.3	0.1	0.1	0.0	0.0	0.0	0.0	0.0	
12	0.1	0.0	0.0	0.0	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
13	0.0	0.0	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
14	0.0	0.0	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
15	0.0	0.0	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
16	0.0	0.0	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
17	0.0	0.0	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
18	0.0	0.0	0.2	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
19	0.0	0.0	0.0	0.0	0.9	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
20	0.0	0.0	0.2	0.0	0.3	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
21	0.0	0.0	0.0	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
22	0.0	0.0	0.0	0.7	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
23	0.0	0.0	0.0	0.1	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
24	0.0	0.0	0.0	0.0	16.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
25	0.0	0.0	0.0	767.2	1.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
26	0.0	0.0	0.0	97.4	0.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
27	0.0	0.0	0.0	15.9	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
28	0.0	0.0	0.0	17.5	0.3	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
29	0.0	0.0	0.0	1.1	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
30	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
31	0.0	0.0	0.0	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
TOTAL	0.1	0.0	0.4	1384.6	46.5	3.0	1.0	0.3	0.0	0.0	0.0	0.0	1,436
Max.day	0.1	0.0	0.2	767.2	16.6	0.4	0.1	0.1	0.0	0.0	0.0	0.0	767

Daily Bedload-Sediment Discharge (tons)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT	
1	0.0	0.0	0.0	0.0	0.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
2	0.0	0.0	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
3	0.0	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
4	0.0	0.0	0.0	43.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
5	0.0	0.0	0.0	4.3	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
6	0.0	0.0	0.0	0.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
7	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
11	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
12	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
13	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
14	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
15	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
18	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
19	0.0	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
21	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
22	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
23	0.0	0.0	0.0	0.0	0.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
24	0.0	0.0	0.0	0.0	1.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
25	0.0	0.0	0.0	76.7	0.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
26	0.0	0.0	0.0	9.7	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
27	0.0	0.0	0.0	1.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
28	0.0	0.0	0.0	1.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
29	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
30	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
31	0.0	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
TOTAL	0.0	0.0	0.0	138.5	4.7	0.3	0.1	0.0	0.0	0.0	0.0	0.0	144
Max.day	0.0	0.0	0.0	76.7	1.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	77

Daily values are based on calculations of sediment discharge at 15-minute intervals.
 Daily values with more than 2 significant figures result from electronic calculations. No additional precision is implied.

Balance Hydrologics, Inc. 800 Bancroft Way, Suite 101, Berkeley, CA 94710 (510) 704-1000; www.balancehydro.com

Form 6. Annual sediment-discharge record, San Francisquito Creek at Piers Lane, water year 2008

Water Year: **2008**
 Stream: San Francisquito Creek
 Station: at Piers Lane **SFPL**
 County: San Mateo County, CA

Daily Suspended-Sediment Discharge (tons)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT	
1	0.0	0.0	0.0	0.0	75.8	0.7	0.1	0.0	0.0	0.0	0.0	0.0	
2	0.0	0.0	0.0	0.0	27.0	0.8	0.1	0.0	0.0	0.0	0.0	0.0	
3	0.0	0.0	0.0	0.0	362.9	0.4	0.1	0.0	0.0	0.0	0.0	0.0	
4	0.0	0.0	0.0	2519.1	21.6	0.5	0.1	0.0	0.0	0.0	0.0	0.0	
5	0.0	0.0	0.0	207.1	5.7	0.4	0.1	0.0	0.0	0.0	0.0	0.0	
6	0.0	0.0	0.0	51.3	2.6	0.3	0.1	0.0	0.0	0.0	0.0	0.0	
7	0.0	0.0	0.1	2.5	1.4	0.3	0.1	0.0	0.0	0.0	0.0	0.0	
8	0.0	0.0	0.0	1.9	0.9	0.3	0.0	0.0	0.0	0.0	0.0	0.0	
9	0.0	0.0	0.0	1.5	0.5	0.3	0.0	0.0	0.0	0.0	0.0	0.0	
10	0.0	0.0	0.0	0.6	0.4	0.3	0.0	0.0	0.0	0.0	0.0	0.0	
11	0.0	0.0	0.0	0.2	0.3	0.2	0.0	0.0	0.0	0.0	0.0	0.0	
12	0.0	0.0	0.0	0.1	0.2	0.2	0.1	0.0	0.0	0.0	0.0	0.0	
13	0.0	0.0	0.0	0.1	0.2	0.2	0.0	0.0	0.0	0.0	0.0	0.0	
14	0.0	0.0	0.0	0.0	0.2	0.2	0.0	0.0	0.0	0.0	0.0	0.0	
15	0.0	0.0	0.0	0.1	0.2	0.2	0.0	0.0	0.0	0.0	0.0	0.0	
16	0.0	0.0	0.0	0.0	0.1	0.2	0.0	0.0	0.0	0.0	0.0	0.0	
17	0.0	0.0	0.0	0.0	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
18	0.0	0.0	1.6	0.0	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
19	0.0	0.0	0.0	0.0	0.3	0.2	0.0	0.0	0.0	0.0	0.0	0.0	
20	0.0	0.0	2.1	0.0	2.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
21	0.0	0.0	0.0	0.0	0.9	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
22	0.0	0.0	0.0	0.5	2.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
23	0.0	0.0	0.0	0.3	3.9	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
24	0.0	0.0	0.0	0.3	76.8	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
25	0.0	0.0	0.0	2784.6	31.4	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
26	0.0	0.0	0.0	929.3	6.6	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
27	0.0	0.0	0.0	67.4	3.6	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
28	0.0	0.0	0.0	66.4	1.9	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
29	0.0	0.0	0.0	9.4	1.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	
30	0.0	0.0	0.0	7.6		0.1	0.0	0.0	0.0	0.0	0.0	0.0	
31	0.0	0.0	0.0	29.8		0.1	0.0	0.0	0.0	0.0	0.0	0.0	
TOTAL	0.1	0.0	3.8	6680.3	630.8	7.3	1.1	0.1	0.0	0.0	0.0	0.0	Qss Annual 7,323
Max.day	0.0	0.0	2.1	2784.6	362.9	0.8	0.1	0.0	0.0	0.0	0.0	0.0	2,785

Daily Bedload-Sediment Discharge (tons)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEPT	
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													Daily bedload discharge was not calculated for WY2008
14													
15													
16													
17													
18													
19													
20													
21													
22													
23													
24													
25													
26													
27													
28													
29													
30													
31													
TOTAL	Qbed Annual ...
Max.day

Daily values are based on calculations of sediment discharge at 15-minute intervals.

Daily values with more than 2 significant figures result from electronic calculations. No additional precision is implied.

Balance Hydrologics, Inc. 800 Bancroft Way, Suite 101, Berkeley, CA 94710 (510) 704-1000; fax: (510) 704-1001

TABLES

Table 1. Station Observer Log: Bear Creek at Sand Hill Road, water year 2008

Site Conditions				Streamflow				Water Quality Observations						High-Water Marks		Remarks	
Date/Time	Observer	Stage	Hydrograph	Measured Discharge	Estimated Discharge	Instrument Used	Estimated Accuracy	Water Temperature	Field Specific Conductance	Adjusted Specific Conductance	pH	Dissolved Oxygen	Dissolved Oxygen	Additional sampling?	Estimated stage at staff plate	Inferred dates?	
(mm/dd/yr)		(feet)	(R/F/S/B)	(cfs)	(cfs)	(AA/PY)	(e/g/f/p)	(oC)	(µmhos/cm)	(at 25 oC)	(pH)	(mg/L)	(% sat.)	(Qbed, etc.)	(feet)	(mm/dd/yr)	
9/24/07 17:35	jg	1.45	B	0.16	...	PY	g	15.9	584	706	grass in creek on gravel bars, frogs chirping
10/26/07 16:30	jo, cg	1.42	B	0.13	...	PY	f	12.4	438	575	8.0	9.4	88%	...	2.0	Oct.12	water is clear, algae on bed, small fish in pool, grass on banks, small leaf dam and vegetation growing at road crossing
11/30/07 14:13	tjb, cg	1.5	B	0.12	...	PY	f	7.7	372	556	8.0	11.3	94%	brown algae on bed, lots of leaves, water clear
12/24/07 15:46	jo, bdb	1.525	B	0.56	0.56	PY	f	7.4	425	640	2.5	Dec.20	water clear; leaves scoured from some areas of bed and deposited in others
1/4/08 16:30	jo, ds	5.8	F	...	512	float	p	10.7	115	159	Qss	6.9	today	water high and turbid; HWM looks about 1.5 feet higher than current level; floating debris still coming down creek
1/6/08 16:21	jo	2.37	F	...	25	V	p	9.3	309	442	Qss	7.2, 4.4, 3.5	Jan.4 and 5	water turbid (6-inch vis.); several recessional HWMs in silt
1/8/08 15:07	tjb, nn	2.13	F	...	8.4	V	p	8.6	371	541	Qss	7.0	Jan. 4	only slightly turbid, 2-foot visibility in water; HWM on downstream staff
1/17/08 17:02	jg	1.87	F	1.55	...	PY	g	6.8	446	683	7 to 7.5	early Jan	HWM is higher than the top of the staff plate which is 6.65
1/25/08 13:06	cg, tjb	3.6	R	...	62.5	V	p	8.1	166	245	Qss	6.5 to 7	early Jan	HWM about 3 feet higher than current water level; significant runoff from hill at time of visit; stage rising ~ 1 in/6min
1/26/08 9:51	cg, tjb	...	F	...	54	R	...	9.3	173	247	Qss	7.0	overnight 1/25-1/26	significant deposits of sand on both bank and HWM 3 feet above current water level, water still turbid
3/7/08 18:30	jg	1.7	B	2.09	...	PY	g	10.8	452	621	8.6	water clear, grasses growing near gate but they only have a small effect on stage, gates open
4/17/08 13:18	jg	1.62	B	0.82	...	PY	g	12.3	516	678	gate is closed, tracks from tractor on sands on right bank, no disturbance to controlling riffle is obvious, small leaf dam
6/3/08 16:27	jo	1.55	B	0.43	...	PY	f-g	15	561	694	7.5	9.2	91%	...	6.9	1/4 or 1/25	water clear, gate closed, 2-3" fish in pool upstream of gate, algae in sunny places
9/26/08 11:10	jo	1.508	B	0.09	...	PY	f	water very turbid and brown at staff; walked upstream and found that water was clear under and above bridge

Notes:

Obs Key: jo is Jonathan Owens, jg is John Gartner, tjb is Travis Baggett, cg is Carla Grandy, nn is Nathan Neufeld, ds is Dave Shaw, bdb is Bonnie de Berry

Stage: Water level observed at outside staff plate

Hydrograph: Describes stream stage as rising (R), falling (F), steady (S), baseflow (B), or diversion underway (D)

Instrument: If measured, typically made using a standard (AA) or pygmy (PY) bucket-wheel ("Price-type") current meter. If estimated, from rating curve(R), visual (V), or float test

Estimated measurement accuracy: Excellent (E) = +/- 2%; Good (G) = +/- 5%; Fair (F) = +/- 9%; Poor (P) estimated percent accuracy given

High-water mark (HWM): Measured or estimated at location of the staff plate

Table 2. Station observer log: Los Trancos Creek at Piers Lane, water year 2008

Site Conditions				Streamflow				Water Quality Observations							High-Water Marks		Remarks
Date/Time	Observer(s)	Stage (staff plate)	Hydrograph	Measured Discharge	Estimated Discharge	Instrument Used	Estimated Accuracy	Water Temperature	Specific Conductance at field temp.	Specific Conductance at 25°C	pH	Dissolved Oxygen	Dissolved Oxygen	Additional sampling?	Estimated stage at staff plate	Inferred dates?	Remarks
(mm/dd/yr)		(feet)	(R/F/S/B/P)	(cfs)	(cfs)	(AA/PY)	(e/g/f/p)	(°C)	(µmhos/cm)	(at 25 °C)	(pH)	(mg/L)	(% sat.)	(Qbed, etc.)	(feet)	(mm/dd/yr)	
9/24/07 11:56	jk	0.61	B	0.02	...	PY	p	14.7	1587	2010	...	7.9	80%	water clear with brown tint, minor leaf dam
10/10/07 12:54	jk	0.75	F	...	0.4	visual	p	15	727	899	Qss	water slightly turbid, brownish, fine or organic material visibility in transport, rain last night and showers this morning, leaf dam gone since last visit
11/19/07 11:44	tjb	0.66	B / F	0.07	0.2	PY	g	12.7	1571	2055	8.6	9.4	88%	...	1.4	last big storm in Oct	water clear, light drizzle in region earlier
12/24/07 12:00	jo, bdb	0.72	B	0.12	0.15	PY	f	8.7	1207	1760	1.2-1.3	12/20/07	water clear; several large leaf + stick dams
1/4/08 10:00	jo, ds	4.70	R	239	...	float	p	Qss(x2)	Los Trancos looks more turbid than San Francisquito, suds in water, Qss samples on rising hydrograph
1/8/08 13:26	tjb, nn	1.09	F	...	2.5	visual	p	9.4	733	1044	Qss	water in creek very clear
1/17/08 9:55	jk	0.75	R	0.36	...	PY	f	7.2	682	1032	8	11.1	92%	...	4.6-4.7	early Jan.	water clear, some eucalyptus bark and leaves make a minor dam
1/25/08 15:25	tjb, cg	5.2	R	297	...	float	p	9	130	188	Qss	upper staff plate broke off in surge of woody debris at 15:20, water turbid
1/26/08 8:36	tjb, cg	~3.95	F	9.0	271	391	Qss	6.0	1/25/08	upper staff plate missing; stage and high water mark estimated, water brown and turbid
2/13/08 10:30	tjb	0.89	B	...	0.25	visual	p	10.2	763	1065	specific conductance probe cleaned of sediment, water clear, about 20+ fish 1-2", recovered and replaced staff plate
3/7/08 14:36	jk	1.03	B	2.19	...	AA	g	11.7	725	970	8.3	8.7	81%	appears to be new sand deposited near staff plate and in pools upstream and downstream of gage, DO probe may be malfunctioning
4/17/08 16:01	jk	0.93	B	0.99	0.5-0.7	PY	g	13.8	840	1067	7.1	10.7	98%	...	3.0, 5.8	Feb., Jan.	water clear, small leaf dam
6/3/08 19:30	jo	0.75	B	0.31	...	PY	f	16.0	1130	1362	7.8	8.3	83%	water clear, many leaves in bed of creek, lowered stilling well, stilling well full of sand and gravel
7/29/08 16:45	jo	0.63	B	0.033	0.05	PY	f	18.4	1612	1846	...	7.8	83%	low flow, water clear, many leaves in creek, including leaf dam just d/s of staff.
9/24/08 15:57	tjb	0.58	B	...	0.045	visual	p	17	1649	1950	8.3	6.9	72%	Probes appear in good condition but could not check the pressure transducers because the stilling well is filled with sediment.

Observer Key: jo= Jonathan Owens; bdb= Bonnie de Berry; jg = John Gartner, nn = Nathan Neufeld; ds = Dave Shaw; tjb = Travis Baggett, cg = Carla Grandy

Stage: Water level observed at outside staff plate

Hydrograph: Describes stream stage as rising (R), falling (F), steady (S), baseflow (B), uncertain (U), or peak (P).

Instrument: If measured, typically made using a standard (AA) or pygmy (PY) bucket-wheel ("Price-type") current meter. If estimated, from rating curve (R) or visual estimate (visual) or float test (float.)

Estimated measurement accuracy: Excellent (E) = +/- 2%; Good (G) = +/- 5%; Fair (F) = +/- 9%; Poor (P) = +/- > 9%

High-water mark (HWM): Measured or estimated at location of the staff plate

Additional Sampling: Qbed = Bedload, Qss = Suspended sediment, WQ = composite water quality sampling, WQgrab = grab samples (typically ammonia or mercury.)

Table 3. Station observer log: San Francisquito Creek at Piers Lane, water year 2008

Site Conditions				Streamflow				Water Quality Observations							High-Water Marks		Remarks
Date/Time	Observer(s)	Stage (staff plate)	Hydrograph	Measured Discharge	Estimated Discharge	Instrument Used	Estimated Accuracy	Water Temperature	Specific Conductance at field temp.	Specific Conductance at 25C	pH	Dissolved Oxygen	Dissolved Oxygen	Additional sampling?	Estimated stage at staff plate	Inferred dates?	
(mm/dd/yr)		(feet)	(R/F/S/B)	(cfs)	(cfs)	(AA/PY)	(e/g/f/p)	(°C)	(µmhos/cm)	(us@25°C)	(pH)	(mg/L)	(% sat.)	(Qbed, etc.)	(feet)	(mm/dd/yr)	
9/24/07 13:13	yg	3.23	B	0.077	...	PY	p	14.7	1132	1411	...	2.7	26%	water clear and brown in color, algae on the bed
10/10/07 12:58	yg	3.42	F	...	~0.8	visual	p	14.9	503	623	water turbid, brownish grey
11/19/07 13:02	tjb	3.34	B	0.21	...	PY	p	12.4	692	912	8.6	7.2	67%	...	3.54	10/12/07	water clear, low velocity, fine sediment on bed easily stirred up, buckeyes dropping into pool, small fish (~1") in pool
12/24/07 12:30	jo, bdb	3.40	B	0.71	1.0	PY	f	7.4	540	814	4.60	12/20/07	water is tea colored and slightly turbid; rocks are extra slippery from algae
1/4/08 12:05	jo, ds	6.90	R	700	...	float	p	Qss(x2)	high flows, high winds, heavy rain earlier, yg and gg stopped by during visit
1/8/08 13:35	tjb, nn	4.05	B	...	13	visual	p	8.4	448	656	Qss	water turbid
1/17/08 10:55	yg	3.62	B	2.84	...	PY	g	6.1	515	801	...	9.8	78%	...	9.5	1/4/08	water very slightly turbid, orange/brown
1/25/08 15:35	tjb, cg	7.15	R	700	...	float	p	8.5	218	328	Qss	high flows, water turbid
1/26/08 8:49	tjb, cg	6.20	F	8.9	191	277	Qss	water turbid
2/13/08 10:46	tjb	3.89	B	...	5	visual	p	9.2	436	625	cleaned specific conductance probe
3/7/08 12:46	yg	4.90	B	8.55	...	AA	f	11.1	544	740	8.0	10.2	94%	water clear, leaves budding out, cleaned sediment from stilling well
4/17/08 14:30	yg	3.65	B	2.59	...	PY	f	13.1	749	955	7.1	9.6	95%	water clear, long, green, filamentous algae on rocks
6/3/08 18:00	jo	3.37	B	0.41	...	PY	f	17.8	915	1062	7.4	17.6	92%	water clear, many 3" fish in pool under bridge, algae on rocks, sand deposits between cobbles at bottom of riffle and head of pool.
7/29/08 17:15	jo	3.24	B	0.063	...	PY	f	19.4	1158	1298	...	9.0	98%	many 2-3" fish in pool under bridge, numerous 1" fish also; pool yellowish-green tint, water in riffle looks clear.
9/24/08 16:39	tjb	3.17	B	...	0.07	visual	p	16.7	1250	1488	8.2	6.7	69%	streamflow upstream of gage pool is among the cobbles and difficult to estimate.

Observer Key: jo= Jonathan Owens; bdb = Bonnie de Berry; ds = Dave Shaw; yg = John Gartner; nn = Nathan Neufeld; tjb = Travis Baggett; cg = Carla Grandy

Stage: Water level observed at outside staff plate

Hydrograph: Describes stream stage as rising (R), falling (F), steady (S), baseflow (B), or uncertain (U).

Instrument: If measured, typically made using a standard (AA) or pygmy (PY) bucket-wheel ("Price-type") current meter. If estimated, from rating curve (R) or visual estimate (visual) or float test (float.)

Estimated measurement accuracy: Excellent (E) = +/- 2%; Good (G) = +/- 5%; Fair (F) = +/- 9%; Poor (P) = +/- > 9%

High-water mark (HWM): Measured or estimated at location of the staff plate

Additional Sampling: Qbed = Bedload, Qss = Suspended sediment, WQ = composite water quality sampling, WQgrab = grab samples (typically ammonia or mercury.)

Table 4. Hydrologic summary for the period of record, Bear Creek at Sand Hill Road, Los Trancos and San Francisquito Creeks at Piers Lane

Water Year ¹	Annual Flow ⁴				Sediment Discharge ⁴				Peak Flow		
	Mean Daily Flow	Maximum Daily Mean Flow	Minimum Daily Mean Flow	Total Flow Volume	Suspended Sediment	% suspended	Bedload Sediment	% bedload	Peak Flow	Peak Stage ⁵	Date Time
	(cfs)	(cfs)	(cfs)	(ac-ft)	(tons)		(tons)		(cfs)	(ft)	(24-hr)
Bear Creek at Sand Hill Road ^{2,6}											
2000	10.65	684	0.01	7,728	24,426	93%	1,778	7%	2,050	8.81	2/13/00 20:45
2001	3.71	113	0.01	2,689	681	87%	98	13%	353	4.26	1/25/01 16:45
2002	5.12	189	0.01	3,704	1,681	91%	171	9%	733	5.78	12/2/01 7:45
2003	6.86	434	0.01	4,965	11,258	94%	762	6%	2,231	9.29	12/16/02 5:45
2004	5.87	282	0.01	4,260	5,624	91%	555	9%	1,186	7.28	1/1/04 12:15
2005	10.77	257	0.01	8,113	2,460	96%	98	4%	487	5.35	12/30/04 21:30
2006	18.33	849	0.01	13,269	11,693	96%	468	4%	3,800	10.70	12/31/05 7:00
2007	1.75	72	0.01	1,269	133	96%	5	4%	197	4.02	2/26/07 23:30
2008	3.36	241	0.01	2,442	1,127	96%	45	4%	862	7.29	1/4/08 14:45
Los Trancos Creek at Piers Lane ³											
2003	2.67	123	0.01	1,934	2,494	649	7.58	12/16/02 6:30
2004	2.70	136	0.02	1,461	2,991	582	5.47	2/25/04 11:00
2005	3.56	67	0.02	2,575	1,424	94%	85	6%	357	4.33	2/18/05 6:00
2006	7.09	190	0.13	5,137	4,328	91%	433	9%	640	7.80	12/31/05 8:15
2007	0.75	11	0.01	540	37	90%	4	10%	44	2.32	12/12/06 9:15
2008	1.80	125	0.02	1,307	1,436	91%	144	9%	316	5.64	1/25/08 18:30
San Francisquito Creek at Piers Lane ³											
2003	15.40	782	0.09	11,146	10,097	2,706	12.46	12/16/02 6:30
2004	11.02	453	0.12	8,002	6,910	1,474	9.67	1/1/04 13:15
2005	24.35	509	0.05	17,627	9,463	749	7.77	2/15/05 21:00
2006	40.09	1,704	0.39	29,027	34,217	4,300	12.98	12/31/05 8:15
2007	4.88	213	0.01	3,533	674	436	6.46	2/27/07 0:45
2008	10.43	551	0.01	7,574	7,323	1,621	8.86	1/25/08 21:30

Notes:

General: Values displaying more than 2 or 3 significant figures are the result of electronic calculations; no additional precision is implied.

- Hydrologic monitoring is conducted by "water years", rather than calendar years, to encompass whole rainfall seasons. Water year 2008 (WY2008) extends from October 1, 2007 through September 30, 2008 and corresponds to the water year used by most federal agencies.
- The period of record for the Bear Creek at Sand Hill Road station is October 12, 1999 to September 30, 2007.
- The period of record for the Piers Lane stations is October 2002 to September 2007; the partial record from the initial season (WY2002) of monitoring is not shown.
- Daily flow values were computed from instantaneous flow calculated at 15-minute intervals. Sediment discharge values were totalled from calculations at 15-minute intervals. "Maximum daily mean flow" is the highest daily mean flow of the year.
- Stage is the staff plate reading; the staff plate is set at an arbitrary datum and does not represent the absolute depth of water in the creek.
- In water year 2006, Bear Creek peak flow (12/31/2005) was estimated using the slope-area method from surveyed high-water marks. Because the gaging equipment was destroyed in the high flows, daily mean flow on that day was calculated from the 15-minute flow record synthesized by correlation with other creeks. Peak flow at the two Piers Lane stations (12/31/2005) were calculated using the slope-area method and surveyed high-water marks (the equipment at Piers Lane was not damaged).

**Table 5. Measurements and calculations of sediment transport,
Bear Creek at Sand Hill Road, water year 2008**

<i>Field Observations</i> ¹						<i>Sediment Transport</i>				
Sample Date:Time	Observer(s)	Stage	Stream Condition	Streamflow Discharge	Streamflow Value Source	Bedload Discharge	Bedload Discharge	Suspended Sediment Concentration	Suspended Sediment Discharge	Turbidity
		(ft)	R,F,B,U	(cfs)	M,R,E	(lb/sec)	(tons/day)	(mg/l)	(tons/day)	(ntu)
Bear Creek at Sand Hill Road										
1/4/08 16:30	jo, ds	5.8	F	512	E	1179	1,628	831
1/6/08 16:15	jo	2.37	F	25	M	20.4	1.38	21
1/8/08 15:10	tjb, nn	2.13	R	8.4	M	26.4	0.60	11.4
1/25/08 13:11	tjb, cg	3.6	R	158.1	M	414.3	176.7	376
1/26/08 9:55	cg, tjb	2.99	F	108.4	R	79.6	23.27	83.1

Notes and explanations

- Observer Key: jo = Jonathan Owens; tjb = Travis Baggett, cg = Carla Grandy, nn = Nathan Neufeld, ds = Dave Shaw
Stream Condition: R = rising, F = falling, B = baseflow, U = uncertain
Streamflow discharge is the measured or estimated instantaneous flow at the time that sediment was sampled. The value is usually taken from the datalogger record and typically differs from the mean flow for the day.
Streamflow Value Source: M = measured; R = rating curve; E = estimated; Streamflow for composite samples is mean flow for the sampling period.
- Active Bed Width is estimated by the field observer as the width through which significant amounts of bedload are being transported.
Sampler Width and Type: 0.25 = 3-inch Helley Smith; 0.50 = 6-inch Helley Smith
- Values for sediment discharge showing more than two to three digits are the result of calculations; increased precision is not implied.
Bedload Discharge (lbs/sec) = [active bed width (ft) * sample dry weight (gm) * 0.002205 (lbs)] / [sampler width (ft) * sampling time (sec)]
Bedload Discharge (tons/day) = [active bed width (ft) * sample dry weight (gm) * 86,400 (sec)] / [sampler width (ft) * sampling time (sec) * 907,200 (gm)]
If the creek is visibly clear, then suspended sediment samples are not collected because concentrations would likely be below the detection limit.

**Table 6. Measurements and calculation of suspended sediment:
San Francisquito and Los Trancos Creeks at Piers Lane, water year 2008**

Field observations			Bedload Sampling Details							Bedload Discharge		Suspended sediment			
Date and Time	Observer	Stage (feet)	Stream Condition (R, F, B)	Discharge (cfs)	Active Bed Width (ft)	Sampler Width (ft)	No. of Verts.	Time/Vert. (sec)	Total Time (sec)	Sample Dry Weight (gm)	Bedload-Sediment Discharge Rate (lb/sec)	Bedload-Sediment Discharge Rate (tons/day)	Total Suspended Solids (mg/L)	Suspended Sediment discharge (tons/day)	Turbidity (NTU)
San Francisquito Creek at Piers Lane															
10/10/07 12:58	jg	3.42	F	0.185	31.4	0.016	29.6
1/4/08 11:28	jg, gg	6.9	R	620	1795	3002	529
1/4/08 12:05	jo, ds	7.5	R	915	1490	3679	665
1/8/08 13:35	tjb, nn	4.05	R	14.7	31.0	1.2	55.4
1/25/08 15:35	tjb, cg	7.15	R	674	1079	1961	333.6
1/26/08 8:49	tjb, cg	6.20	F	346	408.0	381	294
Los Trancos Creek at Piers Lane															
10/10/07 12:54	jg	0.75	F	0.023	7.6	0.0005	5
1/4/08 11:00	jo, ds	4.36	R	190.8	4750	2444	1420
1/4/08 12:00	jo, ds	4.85	R	234.3	5164	3264	1530
1/8/08 13:26	tjb, nn	1.14	F	3.5	7.7	0.073	5.27
1/25/08 15:25	tjb, cg	4.9	R	239.2	4787	3089	920
1/26/08 8:36	tjb, cg	2.27	F	45.5	194.4	23.8	170

Notes:

Observer Key: jo= Jonathan Owens; jg = John Gartner; ds = Dave Shaw; tjb = Travis Baggett; gg = Greg Guensch; cg = Carla Grandy; nn = Nathan Neufeld

Streamflow discharge is the measured or estimated instantaneous flow when sediment was sampled, usually from the datalogger record, and usually differs from the mean flow for the day.

Stream Condition: R = rising, F = falling, B = baseflow, U = uncertain

Values for sediment discharge having more than two to three digits displayed are the result of calculations; increased precision is not implied.

If the creek is visibly clear, then suspended sediment samples are not collected because concentrations would likely be below the detection limit.

Bedload Discharge (lbs/sec) = [active bed width (ft) * sample dry weight (gm) * 0.002205 (lbs)] / [sampler width (ft) * sampling time (sec)]

Bedload Discharge (tons/day) = [active bed width (ft) * sample dry weight (gm) * 86,400 (sec)] / [sampler width (ft) * sampling time (sec) * 907,200 (gm)]

FIGURES





Figure 1. Stream monitoring location in the San Francisquito watershed
 The Piers Lane stations are located just above the confluence of San Francisquito and Los Trancos Creeks. The Bear Creek station is located downstream of Sand Hill Road.







Figure 2. Daily flow hydrographs for San Francisquito, Los Trancos and Bear Creeks, water year 2008. Flow in San Francisquito Creek is generally greater than flow in Bear Creek or Los Trancos Creek, as would be expected from its larger drainage area. Note that the peak 15-minute flow does not necessarily correspond to the highest daily mean flow.





Figure 3. Daily flow hydrograph for Bear Creek at Sand Hill Road, water year 2008. Some flow regulation occurs upstream of this station which sometimes causes irregular flow patterns. The peak flow of the water year was approximately 862 cfs on January 4, 2008 at about 2:45 PM.





Figure 4. Daily flow hydrograph for San Francisquito Creek at Piers Lane, water year 2008. The peak flows on January 4 and January 25 were of similar magnitude (1613 and 1620 cfs, respectively). Both peaks were approximately 2.5-year floods.







Figure 5. Daily flow hydrograph for Los Trancos Creek at Piers Lane, water year 2008.

Baseflow was low at both the beginning and end of the water year, reflecting the below average rainfall during water years 2007 and 2008. The peak flows on January 4 and 25 were of similar magnitude (255 and 316 cfs, respectively), and were both approximately 2.5-year floods.







Figure 6. Unit flow hydrographs for San Francisquito, Los Trancos and Bear Creeks, water year 2008. Unit flow is calculated by normalizing flow by watershed area. In many cases, lower flows in one creek as compared to the other creeks may be due to diversions, but flows can also be influenced by geology, topography and weather patterns.





Figure 7. Cumulative 15-minute precipitation record at Bear Creek at Sand Hill Road, and San Francisquito Creek at Piers Lane, water year 2008. Total rainfall for water year 2008 was 82 to 92 percent of average. The different totals between the two stations illustrate the typical annual gradient within the watershed, linked to distance from the top of the Santa Cruz Mountains.






Figure 8. Specific conductance measurements, Los Trancos Creek at Piers Lane, water years 2002 to 2008. Specific conductance of baseflow during water year 2008 is at the high end of previous measurements; this would be expected during a low-rainfall year when more of the baseflow is derived from groundwater with a long flow path.





Balance Hydrologics, Inc.[®]

Figure 9. Specific conductance measurements, Bear Creek at Sand Hill Road, water years 2004 to 2008. Specific conductance measurements are generally similar for all years, with lower values during storms. The water year 2008 flow record is plotted for reference.





Figure 10. Specific conductance measurements, San Francisquito Creek at Piers Lane, water years 2002 to 2008. Specific conductance measurements are generally similar for all years, with lower values during storms. This year, values were generally at the low end of the range during the fall due to early-season rainfall, and values are in the mid-to-high range during the winter and spring of 2008, as expected during a relatively low rainfall year. The WY08 flow record is plotted for reference.





Figure 11. Daily water temperature record for San Francisquito Creek at Piers Lane, water year 2008. Temperature patterns are similar at the San Francisquito Creek, Los Trancos Creek and Bear Creek stations. Water temperature generally seems to be slightly cooler in San Francisquito Creek than in Los Trancos Creek during the winter and warmer during the summer.





Figure 12. Daily water temperature record for Los Trancos Creek at Piers Lane, water year 2008. Temperature patterns are similar at the San Francisquito Creek, Los Trancos Creek and Bear Creek stations. Water temperature generally seems to be slightly warmer in Los Trancos Creek than in San Francisquito Creek during the winter and cooler during the summer.





Figure 13. Daily water temperature record for Bear Creek at Sand Hill Road, water year 2008.

Temperature patterns at this station were similar to the downstream station, San Francisquito Creek at Piers Lane. Summer temperatures are lower at Bear Creek than either of the Piers Lane Stations.






Figure 14. pH measurements in San Francisquito Creek, Los Trancos Creek and Bear


Creek, water year 2008. Field measurements were made with hand-held pH meters. The instream pH probes did not work properly at any of the three stations. The Bear Creek water year 2008 daily mean flow record is plotted for reference.



Balance Hydrologics, Inc.®

Figure 15. Dissolved oxygen concentrations in Bear Creek at Sand Hill Road, water year 2008.

Field measurements by Balance staff indicate that dissolved oxygen concentrations are lower during late summer and fall low flows when water temperatures are higher, stream turbulence is lower, and products of decomposing leaves often create localized oxygen demand. The flow and temperature records are plotted for reference.



Balance Hydrologics, Inc.[®]

Figure 16. Dissolved oxygen concentrations in Los Trancos Creek at Piers Lane, water year 2008.

Dissolved oxygen levels in Los Trancos Creek are almost always close to 100% saturation. Field measurements by Balance staff indicate that dissolved oxygen concentrations are lower during late summer and fall low flows when water temperatures are higher, stream turbulence is lower, and products of decomposing leaves often create localized oxygen demand. The flow record is plotted for reference.





Figure 17. Dissolved oxygen concentrations in San Francisquito Creek at Piers Lane, water year 2008. Field measurements by Balance staff indicate that dissolved oxygen concentrations are lower during late summer and fall low flows when water temperatures are higher, stream turbulence is lower, and products of decomposing leaves often create localized oxygen demand.





Figure 18. Sediment measurements and rating curves for the Piers Lane stations. The samples collected this year show a similar relationship as in previous years, therefore we did not change the sediment rating curves from water year 2007.



Balance Hydrologics, Inc.®

Figure 19. Sediment measurements and rating curves for Bear Creek at Sand Hill Road, water years 1998-2008.

Suspended sediment as a function of flow is similar in water year 2008 to the previous year. No bedload discharge was measured in water year 2008.

APPENDICES

APPENDIX A

Laboratory Results (Piers Lane and Bear Creek stations)

SOIL CONTROL LAB



2008 LAB
WY2008

Account Number:
8010436-37-4205

Balance Hydrologics
841 Folger Ave.
Berkeley, CA 94710
Attn: Jonathan Owens

Reporting Date:
January 23, 2008

Date Received: Water samples received January 17, 2008
Project #/Name: Various / Various
Laboratory #: 8010436-1/37 through 25/37

Sample Identification	Turbidity (NTU)	Particles Larger Than 63 Micron	Suspended Solids Smaller Than 63 Micron	Total Suspended Solids (mg/L)
SMVW 071206:1300	127.6	2.7	47.8	50.5
ECDM 080108:1320	3.85	1.7	5.1	6.8
DNST 010408:1545	296	183.6	262.8	446.4
DEER 010408:1500	1132	954.5	1391.3	2345.8
→ LTPL 080108:1326	5.27	0.6	7.1	7.7
→ LTPL 071010:1254	4.56	2.8	4.8	7.6
→ LTPL 080104:1100	1420	2651.1	2098.7	4749.8
→ LTPL 080104:1200	1530	2995.0	2168.9	5163.9
LTAA 080106:1435	18.1	2.0	21.3	23.3
LTAA 071218:0945	30.8	0.0	29.5	29.5
LTAA 080108:1420	11.1	1.3	14.7	16.0
LTAA 080104:1525	1580	1704.8	1969.0	3673.8
LTAA 080104:1340	1430	2297.4	1815.6	4113.0
→ BCSH 080108:1510	11.4	0.0	26.4	26.4
→ BCSH 080104:1630	831	19.3	1159.7	1179.0
→ BCSH 080106:1615	21	1.6	18.8	20.4
WCVR 080104:0820	144	51.6	195.1	246.7
WCVR 080104:0854	120	125.2	214.0	339.2
CMWR 080104:1320	4440	3171.6	6173.9	9345.5
CMWR 071218:1005	20.4	4.0	36.7	40.6
CMWR 080106:1505	50.3	1.8	51.2	53.0
SVSV 080104:1607	164	38.0	134.2	172.2
SVSV 080106:1555	163	1.4	86.4	87.8
SHEP O/S 080108:1252	55.1	0.0	28.1	28.1
SHEP O/S 080108:1250	57.1	0.0	26.8	26.8

Mike Galloway

SOIL CONTROL LAB



Account Number:
8010436-37-4205

Balance Hydrologics
841 Folger Ave.
Berkeley, CA 94710
Attn: Jonathan Owens

Reporting Date:
January 23, 2008

Date Received: Water samples received January 17, 2008
Project #/Name: Various / Various
Laboratory #: 8010436-26/37 through 37/37

Sample Identification	Turbidity (NTU)	Particles Larger Than 63 Micron	Suspended Solids Smaller Than 63 Micron	Total Suspended Solids (mg/L)
SHEP O/S 080108:1227	54.3	0.0	19.7	19.7
→ SFPL 080108:1224	56.1	0.0	48.9	48.9
→ SFPL 071010:1258	29.6	0.6	30.8	31.4
→ SFPL 080108:1335	55.4	2.4	28.6	31.0
→ SFPL 080104:1110	529	1146.7	648.2	1794.9
→ SFPL 080104:1205	665	671.6	818.8	1490.4
K4 080104:1249	461	444.6	649.8	1094.4
K4 080104:1150	421	541.2	596.8	1138.0
San Geramino 122007:0900	32.1	3.9	18.4	22.3
K4 080104:1511	59	237.3	346.3	583.7
K4 010908:1100	23.9	2.0	20.8	22.8
CMWR 080108:1440	23.4	3.4	18.7	22.1

Mike Galloway

SOIL CONTROL LAB

202018 LAB

WY2008

Account Number:
8020669-42-4205

Balance Hydrologics
841 Folger Ave.
Berkeley, CA 94710
Attn: Jonathan Owens

Reporting Date:
March 30, 2008

Date Received: Water samples received February 26, 2008
Project #/Name: Various / Various
Laboratory #: 8020669-1/42 through 25/42

Sample Identification	Turbidity (NTU)	Particles Larger Than 63 Micron	Suspended Solids Smaller Than 63 Micron	Total Suspended Solids (mg/L)
K4 02/08/08:1030	4.69	0.0	3.6	3.6
K4 01/25/08:1838	374	7567.3	405.5	7972.8
K4 01/25/08:1840	372	658.0	435.2	1093.2
SG K4 02/19/08:0915	4.32	0.0	11.0	11.0
→ SFPL 01/25/08:1535	333.6	700.1	378.7	1078.8
→ SFPL 01/26/08:0849	294	138.4	269.6	408.0
SHEP Downstream 01/25/08:121:	50.1	42.3	65.0	107.3
SHEP U/S 01/26/08:1150	77.5	9.6	78.1	87.8
WCVR 01/27/08:1410	156.2	100.7	220.0	320.7
WCVR 01/28/08:1415	144.2	55.1	297.5	352.5
LTAA 01/28/08:1032	43.9	11.4	36.5	47.9
LTAA 01/25/08:1400	974	815.5	1322.5	2138.0
LTAA 01/25/08:1602	902	2117.7	1208.3	3326.0
LTAA 01/26/08:0905	98.6	11.1	100.3	111.4
ECDM 02/03/08:0845	40.1	12.6	46.1	58.7
ECDM 02/03/08:0958	38.5	5.6	35.2	40.8
ECDM 01/25/08:1800	196.2	97.7	266.1	363.8
ECDM 01/25/08:1655	154.4	103.8	242.2	346.1
CMWR 01/25/08:1650	2180	2212.0	3582.7	5794.6
CMWR 01/25/08:0808	3480	59.0	497.7	556.7
CMWR 01/25/08:1645	2150	2388.9	3672.0	6060.9
CMWR 01/28/08:1100	167	12.1	217.1	229.2
PPMP 02/24/08:0908	157	2.0	22.9	24.9
DNST 01/25/08:1445	664	255.5	488.7	744.2
DNST 02/24/08:0836	35.4	2.4	19.3	21.7

Mike Galloway

SOIL CONTROL LAB



Account Number:
8020669-42-4205

Balance Hydrologics
841 Folger Ave.
Berkeley, CA 94710
Attn: Jonathan Owens

Reporting Date:
March 30, 2008

Date Received: Water samples received February 26, 2008
Project #/Name: Various / Various
Laboratory #: 8020669-26/42 through 42/42

<u>Sample Identification</u>	<u>Turbidity (NTU)</u>	<u>Particles Larger Than 63 Micron</u>	<u>Suspended Solids Smaller Than 63 Micron</u>	<u>Total Suspended Solids (mg/L)</u>
DEER 01/25/08:1635	1120	754.0	1228.7	1982.7
DEER 02/24/08:0725	87	31.8	98.2	129.9
→ BCSH 01/26/08:0955	83.1	7.0	72.6	79.6
→ LTPL 01/26/08:0836	170	26.0	168.5	194.4
→ LTPL 01/25/08:1525	920	3550.6	1236.6	4787.1
LTAA 02/04/08:1245	19.9	0.0	22.2	22.2
→ BCSH 01/25/08:1311	376	42.2	372.0	414.3
SEARS 01/26/08:0931	287.2	0.0	246.8	246.8
SEARSVILLE DS 01/17/08:1608	23.6	0.0	15.2	15.2
SEARSVILLE 01/25/08:1336	17	10.7	19.9	30.5
SEARSVILLE 02/04/08:1354	89.8	0.0	63.1	63.1
Lid.Sp 02/05/08:12:30	4.05	0.0	6.4	6.4
Upper Majors 01/26/08:08:46	55.2	189.4	64.7	254.1
Lid.Sp 01/26/08:08:30	100	14.9	125.1	140.0
UMC 01/25/08:16:21	416	185.7	605.2	790.9
Upper Majors 01/26/08:08:35	60	83.3	78.0	161.2
EBØC 01/26/08:09:11	156	37.5	169.8	207.3

Mike Galloway